



Transportation & Site Engineering
Creating Order Since 1966

8365 Keystone Crossing, Suite 201
Indianapolis, IN 46240

Phone: (317) 202-0864 Fax: (317) 202-0908



TRAFFIC IMPACT STUDY

McCordsville, Indiana

PREPARED FOR



OCTOBER 2021

COPYRIGHT

This analysis and the ideas, designs, concepts, and data contained herein are the exclusive intellectual property of A&F Engineering Co., LLC and are not to be used or reproduced in whole or in part, without the written consent of A&F Engineering Co., LLC.

©2021, A&F Engineering Co., LLC

TABLE OF CONTENTS

TABLE OF CONTENTS	II
LIST OF FIGURES	III
CERTIFICATION	IV
INTRODUCTION AND PURPOSE	1
SCOPE OF WORK	1
DESCRIPTION OF THE PROPOSED DEVELOPMENTS	2
STUDY AREA	3
DESCRIPTION OF ABUTTING STREET SYSTEM	5
TABLE 1 – DESCRIPTION OF THE ABUTTING STREET SYSTEM	5
EXISTING TRAFFIC VOLUMES & PEAK HOURS	5
YEAR 2041 BACKGROUND TRAFFIC VOLUMES	5
GENERATED TRAFFIC VOLUMES FROM THE PROPOSED DEVELOPMENTS	5
TABLE 2 – TOTAL GENERATED TRIPS FROM BROADVIEW FARMS DEVELOPMENT	7
TABLE 3 – TOTAL GENERATED TRIPS FROM COLONNADE DEVELOPMENT	7
TABLE 4 – TOTAL GENERATED TRIPS FROM JACOBI LEGACY FARMS DEVELOPMENT	7
TABLE 5 – TOTAL GENERATED TRIPS FROM MCCORD SQUARE DEVELOPMENT	7
TABLE 6 – TOTAL GENERATED TRIPS FROM TOWER DEVELOPMENT	7
PASS-BY & INTERNAL TRIPS	8
TABLE 7 – PASS-BY AND INTERNAL TRIP REDUCTIONS FOR THE PROPOSED MCCORD SQUARE DEVELOPMENT	8
TABLE 8 – PASS-BY AND INTERNAL TRIP REDUCTIONS FOR THE PROPOSED TOWER DEVELOPMENT	9
ASSIGNMENT AND DISTRIBUTION OF GENERATED TRIPS	9
GENERATED TRIPS ADDED TO THE STREET SYSTEM	10
TURN LANE ANALYSIS	14
TABLE 9 – TURN LANE WARRANT RESULTS	14
CAPACITY ANALYSIS	15
CAPACITY ANALYSIS SCENARIOS	16
TABLE 10 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & CR 700 N/PROPOSED BROADVIEW FARMS SOUTH ACCESS DRIVE (INT 1)	16
TABLE 11 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & CR 750 N (INT 2)	17
TABLE 12 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & 2 ND STREET/PROPOSED MCCORD SQUARE ACCESS DRIVE (INT 3)	17
TABLE 13 – LEVEL OF SERVICE SUMMARY: SR 234 & BROADWAY (INT 4)	17
TABLE 14 – LEVEL OF SERVICE SUMMARY: SR 234 & CR 500 W (INT 5)	18
TABLE 15 – LEVEL OF SERVICE SUMMARY: CR 750 N & CR 500 W (INT 6)	18
TABLE 16 – LEVEL OF SERVICE SUMMARY: CR 700 N & 500 W (INT 7)	18
TABLE 17 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & PROPOSED BROADVIEW FARMS NORTH ACCESS DRIVE (INT 8)	18
TABLE 18 – LEVEL OF SERVICE SUMMARY: CR 750 N & MCCORD STREET/PROPOSED BROADVIEW FARMS ACCESS DRIVE (INT 9)	19
TABLE 19 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED MCCORD SQUARE EAST ACCESS DRIVE/PROPOSED COLONNADE EAST ACCESS DRIVE (INT 10)	19

TABLE 20 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED MCCORD SQUARE WEST ACCESS DRIVE (INT 11)	19
TABLE 21 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED MCCORD SQUARE TOWNHOME ACCESS DRIVE (INT 12)	19
TABLE 22 – LEVEL OF SERVICE SUMMARY: BROADWAY & PROPOSED MCCORD SQUARE WEST ACCESS DRIVE (INT 13)	20
TABLE 23 – LEVEL OF SERVICE SUMMARY: BROADWAY & PROPOSED MCCORD SQUARE EAST ACCESS DRIVE (INT 14)	20
TABLE 24 – LEVEL OF SERVICE SUMMARY: SR 234 & PROPOSED MCCORD SQUARE ACCESS DRIVE (INT 15)	20
TABLE 25 – LEVEL OF SERVICE SUMMARY: CR 700 N & PROPOSED COLONNADE ACCESS DRIVE (INT 16)	20
TABLE 26 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED COLONNADE WEST ACCESS DRIVE (INT 17)	21
TABLE 27 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED JACOBI LEGACY FARMS WEST ACCESS DRIVE (INT 18)	21
TABLE 28 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED JACOBI LEGACY FARMS MAIN ACCESS DRIVE (INT 19)	21
TABLE 29 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED JACOBI LEGACY FARMS EAST ACCESS DRIVE (INT 20)	21
TABLE 30 – LEVEL OF SERVICE SUMMARY: CR 500 W & PROPOSED JACOBI LEGACY FARMS ACCESS DRIVE (INT 21)	22
TABLE 31 – LEVEL OF SERVICE SUMMARY: MCCORD SQUARE ACCESS DRIVE & JACOBI LEGACY FARMS ACCESS DRIVE (INT 22)	22
CONCLUSIONS & RECOMMENDATIONS	22

LIST OF FIGURES

FIGURE 1: AREA MAP	4
FIGURE 2: EXISTING TRAFFIC VOLUMES	6
FIGURE 3A: ASSIGNMENT AND DISTRIBUTION OF GENERATED TRAFFIC VOLUMES FROM PROPOSED DEVELOPMENTS (RESIDENTIAL)	11
FIGURE 3B: ASSIGNMENT AND DISTRIBUTION OF GENERATED TRAFFIC VOLUMES FROM PROPOSED DEVELOPMENTS (RETAIL & OFFICE)	12
FIGURE 4: SUM OF YEAR 2041 BACKGROUND TRAFFIC VOLUMES AND GENERATED TRAFFIC VOLUMES FROM PROPOSED DEVELOPMENTS	13


CERTIFICATION

I certify that this **TRAFFIC IMPACT STUDY** has been prepared by me and under my immediate supervision and that I have experience and training in the field of traffic and transportation engineering.

A&F ENGINEERING Co., LLC



R. Matt Brown, P.E.



Antoun Fadoul, E.I.



Trevor Reich, E.I.

INTRODUCTION AND PURPOSE

This **TRAFFIC IMPACT STUDY**, prepared at the request of the Town of McCordsville, focuses on traffic improvements of five proposed future developments that will be located within the town.

The purpose of this analysis is to determine what impact the traffic generated by the proposed developments will have on the existing adjacent roadway system. This analysis will identify any existing roadway deficiencies or ones that may occur when the sites are developed.

Conclusions will be reached that will determine if the roadway system can accommodate the anticipated traffic volumes or will determine the modifications that will be required to the system if there are identified deficiencies.

Recommendations will be made that will address the conclusions resulting from this analysis. These recommendations will address feasible roadway system improvements to provide safe ingress and egress, to and from the proposed developments, with minimal interference to traffic on the public street system.

SCOPE OF WORK

The scope of work for this analysis is as follows:

First, obtain turning movement traffic volume counts between the hours of 6:30 A.M. to 8:30 A.M. and 4:30 P.M. to 6:30 P.M. during a typical weekday in September 2021 at the following study intersections:

- Mt. Comfort Road & CR 700 N
- Mt. Comfort Road & CR 750 N
- Mt. Comfort Road & 2nd Street
- SR 234 & Broadway
- SR 234 & CR 500 W
- CR 750 N & CR 500 W
- CR 700 N & CR 500 W

Second, estimate year 2041 background traffic volumes at the study intersections by applying an annual growth rate to the existing traffic counts.

Third, estimate the number of peak hour trips that will be generated by the proposed developments.

Fourth, assign and distribute the generated traffic from the proposed developments to the study intersections.

Fifth, prepare a capacity analysis, level of service analysis, and turn lane analysis for each of the following scenarios:

Scenario 1: Existing Traffic Volumes – Based on existing peak hour traffic volumes.

Scenario 2: Year 2041 Proposed Development Traffic Volumes – Based on the sum of calculated year 2041 background traffic volumes and generated traffic from the proposed developments.

Sixth, prepare recommendations for the roadway geometrics that will be needed to accommodate the total traffic volumes once the proposed developments are constructed.

Finally, prepare a **TRAFFIC IMPACT STUDY** report documenting all data, analyses, conclusions, and recommendations to provide for the safe and efficient movement of traffic through the study area.

DESCRIPTION OF THE PROPOSED DEVELOPMENTS

Five developments were considered in this study. The following is a description of each proposed development.

BROADVIEW FARMS

The Broadview Farms development is located along Mt. Comfort Road south of CR 750 N. The proposed development will consist of 281 single-family homes and 148 multifamily units. As proposed, Broadview Farms will be served by two full access drives along Mt. Comfort Road, one full access drive along CR 750 N, and two connections to the existing Woods at Gateway Crossing development to the west.

COLONNADE

The Colonnade development is located between CR 750 N and CR 700 N east of Mt. Comfort Road. The proposed development will consist of 199 single-family homes and 77 multifamily units. As proposed, Colonnade will be served by two full access drives along CR 750 N and one full access drive along CR 700 N.

JACOBI LEGACY FARMS

The Jacobi Legacy Farms development is located along CR 750 N west of CR 500 W. The proposed development will consist of 359 single-family homes and 74 multifamily units. As proposed, Jacobi Legacy Farms will be served by three full access drives along CR 750 N, one full access drive along CR 500 W, and a connection of the proposed McCord Square development to the west.

MCCORD SQUARE

The McCord Square development is located north of CR 750 N and south of Broadway and SR 234. McCord Square will consist of 462 multifamily units, 74,000 square feet of various retail land

uses, and 12,000 square feet of various office land uses. As proposed, the development will be serviced by three full access drives along CR 750 N, one full access drive along Mt. Comfort Road, two full access drives along Broadway, one full access drive along SR 234, and a connection to the proposed Jacobi Legacy Farms development to the east.

TOWER

The Tower development is located north of CR 750 N and south of Broadway and SR 234. The site will consist of 50 single-family homes, 52 multifamily units, 73,000 square feet of various retail land uses, and 13,000 square feet of various office land uses. As proposed, the development will be serviced by three full access drives along CR 750 N, one full access drive along Mt. Comfort Road, two full access drives along Broadway, one full access drive along SR 234, and a connection to the proposed Jacobi Legacy Farms development to the east.

Figure 1 is an area map showing the location of the proposed developments.

STUDY AREA

The study area for this analysis has been defined to include the following intersections:

- Mt. Comfort Road & CR 700 N/Proposed Broadview Farms South Access Drive
- Mt. Comfort Road & CR 750 N
- Mt. Comfort Road & 2nd Street/Proposed McCord Square Access Drive
- SR 234 & Broadway
- SR 234 & CR 500 W
- CR 750 N & CR 500 W
- CR 700 N & CR 500 W
- Mt. Comfort Road & Proposed Broadview Farms North Access Drive
- CR 750 N & McCord Street/Proposed Broadview Farms Access Drive
- CR 750 N & Proposed McCord Square East Access Drive/Proposed Colonnade East Access Drive
- CR 750 N & Proposed McCord Square West Access Drive
- CR 750 N & Proposed McCord Square Townhome Access Drive
- Broadway & Proposed McCord Square West Access Drive
- Broadway & Proposed McCord Square East Access Drive
- SR 234 & Proposed McCord Square Access Drive
- CR 700 N & Proposed Colonnade Access Drive
- CR 750 N & Proposed Colonnade West Access Drive
- CR 750 N & Proposed Jacobi Legacy Farms West Access Drive
- CR 750 N & Proposed Jacobi Legacy Farms Main Access Drive
- CR 750 N & Proposed Jacobi Legacy Farms East Access Drive
- CR 500 W & Proposed Jacobi Legacy Farms Access Drive
- McCord Square Access Drive & Jacobi Legacy Farms Access Drive




FIGURE 1
AREA MAP

TRAFFIC IMPACT STUDY
TOWN OF MCCORDSVILLE
MCCORDSVILLE, IN

DESCRIPTION OF ABUTTING STREET SYSTEM

The proposed developments will be primarily served by the public roadway system that includes Mt. Comfort Road, CR 500 W, Broadway, SR 234, CR 750 N, CR 700 N, 2nd Street, and McCord Street.

TABLE 1 – DESCRIPTION OF THE ABUTTING STREET SYSTEM

STREET NAME	NUMBER OF LANES	SPEED LIMIT (MPH)	FUNCTIONAL CLASSIFICATION
Mt. Comfort Road	2	30/40	Principle Arterial
CR 500 W	2	50	Local Road
Broadway	2/4	40	Minor Arterial
SR 234	2	55	Major Collector
CR 750 N	2	45	Major Collector/Local Road
CR 700 N	2	45	Local Road
2 nd Street	2	25	Local Road
McCord Street	2	25	Local Road

EXISTING TRAFFIC VOLUMES & PEAK HOURS

Turning movement traffic volume counts were collected by A&F Engineering between the hours of 6:30 AM to 8:30 AM and 4:30 PM to 6:30 PM during a typical weekday in September 2021 under good weather conditions. According to the turning movement counts, the AM and PM peak hours vary slightly at each study intersection. Hence, the actual peak hours were used at each study intersection to create a “worse-case” scenario. **Figure 2** is a summary of the existing traffic volumes. The intersection count output summary sheets are included in the **Appendix**.

YEAR 2041 BACKGROUND TRAFFIC VOLUMES

In order to account for growth in background traffic volumes, an annual growth rate is applied to the existing traffic volumes. For this analysis, a 0.5% per year growth rate was applied. Therefore, a growth factor of 1.1 was applied to the existing traffic volumes. The year 2041 background traffic volumes are shown in the **Appendix**.

GENERATED TRAFFIC VOLUMES FROM THE PROPOSED DEVELOPMENTS

The estimate of newly generated traffic is a function of the development size and of the character of the land use. The *ITE Trip Generation Manual*¹ was used to calculate the number of trips that will be generated by each of the proposed developments. This report is a compilation of trip data for various land uses as collected by transportation professionals throughout the United States in order to establish the average number of trips generated by those land uses. The following tables summarize the total trips that will be generated by each of the proposed developments.

¹ *Trip Generation Manual*, Institute of Transportation Engineers, Tenth Edition, 2017.





FIGURE 2
EXISTING TRAFFIC
VOLUMES

LEGEND
XX = A.M. PEAK HOUR
(XX) = P.M. PEAK HOUR
* = NEGLIGIBLE

TRAFFIC IMPACT STUDY
TOWN OF MCCORDSVILLE
MCCORDSVILLE, IN

TABLE 2 – TOTAL GENERATED TRIPS FROM BROADVIEW FARMS DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK HOUR		PM PEAK HOUR	
			ENTER	EXIT	ENTER	EXIT
Single-Family Housing	210	281 DU	51	153	173	101
Multifamily Housing	220	148 DU	16	53	53	31
TOTAL			67	206	226	132

TABLE 3 – TOTAL GENERATED TRIPS FROM COLONNADE DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK HOUR		PM PEAK HOUR	
			ENTER	EXIT	ENTER	EXIT
Single-Family Housing	210	199 DU	37	109	124	73
Multifamily Housing	220	77 DU	9	28	30	17
TOTAL			46	137	154	90

TABLE 4 – TOTAL GENERATED TRIPS FROM JACOBI LEGACY FARMS DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK HOUR		PM PEAK HOUR	
			ENTER	EXIT	ENTER	EXIT
Single-Family Housing	210	359 DU	65	195	219	128
Multifamily Housing	220	74 DU	8	28	28	17
TOTAL			73	223	247	145

TABLE 5 – TOTAL GENERATED TRIPS FROM MCCORD SQUARE DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK HOUR		PM PEAK HOUR	
			ENTER	EXIT	ENTER	EXIT
Multifamily Housing	220	462 DU	47	157	146	85
Shopping Center	820	74,000 SF	117	72	209	226
General Office	710	12,000 SF	33	5	2	13
TOTAL			197	234	357	324

TABLE 6 – TOTAL GENERATED TRIPS FROM TOWER DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK HOUR		PM PEAK HOUR	
			ENTER	EXIT	ENTER	EXIT
Single-Family Housing	210	50 DU	10	30	33	19
Shopping Center	820	73,000 SF	117	71	206	224
Multifamily Housing	220	52 DU	6	20	21	12
General Office	710	13,000 SF	34	5	3	13
TOTAL			167	126	263	268

PASS-BY & INTERNAL TRIPS

Pass-by trips are trips that are already in the existing traffic stream along the adjacent public roadway system that enter a site, utilize the site, and then return back to the existing traffic stream. Residential developments usually do not generate a significant number of pass-by trips. However, retail land uses typically generate a significant number of pass-by trips. Therefore, the pass-by trip procedures outlined within the ITE *Trip Generation Handbook*² were used to estimate the pass-by trips for the McCord Square and Tower developments.

An internal trip results when a trip is made between two or more land uses without traversing the external public roadway system. The Broadview Farms, Colonnade, and Jacobi Legacy Farms are all a single land use and as a result, will not generate internal trips. However, the McCord Square and Tower developments will generate internal trips based on the procedures in the ITE *Trip Generation Handbook*. A summary of trip reductions for the proposed developments are shown in **Table 7** and **Table 8**.

TABLE 7 – PASS-BY AND INTERNAL TRIP REDUCTIONS FOR THE PROPOSED MCCORD SQUARE DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK		PM PEAK	
			IN	OUT	IN	OUT
Multifamily Housing	220	462 DU	47	157	146	85
		Internal Trips	1	3	59	22
		External Trips	46	154	87	63
Shopping Center	820	74k SF	117	72	209	226
		Internal Trips	3	2	24	60
		External Trips	114	70	185	166
		External Pass-By Trips	24	24	56	56
		External Non-Pass-By Trips	90	46	129	110
General Office	710	12k SF	33	5	2	13
		Internal Trips	2	1	2	3
		External Trips	31	4	0	10
TOTAL TRIPS			197	234	357	324
INTERNAL TRIPS			6	6	85	85
EXTERNAL TRIPS			191	228	272	239
EXTERNAL PASS-BY TRIPS			24	24	56	56
EXTERNAL NON-PASS-BY TRIPS			167	204	216	183

² *Trip Generation Handbook*, Institute of Transportation Engineers, 2004.

TABLE 8 – PASS-BY AND INTERNAL TRIP REDUCTIONS FOR THE PROPOSED TOWER DEVELOPMENT

DEVELOPMENT INFORMATION			GENERATED TRIPS			
LAND USE	ITE CODE	SIZE	AM PEAK		PM PEAK	
			IN	OUT	IN	OUT
Single-Family Housing	210	50 DU	10	30	33	19
Internal Trips			0	1	15	9
External Trips			10	29	18	10
Shopping Center	820	73k SF	117	71	206	224
Internal Trips			1	1	16	26
External Trips			116	70	190	198
External Pass-By Trips			24	24	65	65
External Non-Pass-By Trips			92	46	125	133
Multifamily Housing	210	52 DU	6	20	21	12
Internal Trips			0	0	10	5
External Trips			6	20	11	7
General Office	710	12k SF	34	5	3	13
Internal Trips			2	1	2	3
External Trips			32	4	1	10
TOTAL TRIPS			167	126	263	268
INTERNAL TRIPS			3	3	43	43
EXTERNAL TRIPS			164	123	220	225
EXTERNAL PASS-BY TRIPS			24	24	65	65
EXTERNAL NON-PASS-BY TRIPS			140	99	155	160

ASSIGNMENT AND DISTRIBUTION OF GENERATED TRIPS

The study methodology used to determine the traffic volumes from the site that will be added to the street system is defined as follows:

1. The volume of traffic that will enter and exit the proposed developments must be assigned to the access points and to the public street system. Using the traffic volume data collected for this analysis, traffic to and from the developments have been assigned to the proposed driveways and to the public street system that will be serving the site.
2. To determine the volumes of traffic that will be added to the public roadway system, the generated traffic must be distributed by direction to the public roadways at their intersection with the driveways. For the proposed developments, the trip distribution was based on the location of the developments, the existing traffic patterns, and the assignment of generated traffic.

Figure 3A and **Figure 3B** illustrate the assignment and distribution of generated traffic volumes for the proposed developments.

GENERATED TRIPS ADDED TO THE STREET SYSTEM

The generated traffic volumes that can be expected from the proposed developments have been assigned to each of the study intersections. These volumes were determined based on the previously discussed trip generation data, assignment of generated traffic, and distribution of generated traffic. The total peak hour generated traffic volumes from the proposed developments are shown in the **Appendix**.

Figure 4 shows the sum of year 2041 background traffic volumes and generated traffic volumes from the proposed developments.

DRAFT




FIGURE 3A
ASSIGNMENT & DISTRIBUTION
OF GENERATED TRAFFIC VOLUMES
FROM PROPOSED DEVELOPMENTS
(RESIDENTIAL)

TRAFFIC IMPACT STUDY
TOWN OF MCCORDSVILLE
MCCORDSVILLE, IN




FIGURE 3B
ASSIGNMENT & DISTRIBUTION
OF GENERATED TRAFFIC VOLUMES
FROM PROPOSED DEVELOPMENTS
(RETAIL & OFFICE)

TRAFFIC IMPACT STUDY
TOWN OF MCCORDSVILLE
MCCORDSVILLE, IN



TURN LANE ANALYSIS

The generated peak hour traffic volumes were combined with year 2041 background traffic volumes to determine if turn lanes would be required along Mt. Comfort Road, Broadway, CR 500 W, SR 234, CR 750 N, or CR 700 N at the access drive locations. This analysis was done in accordance with the INDOT *Driveway Permit Manual*³. The results are summarized in the following table.

TABLE 9 – TURN LANE WARRANT RESULTS

LOCATION	SCENARIO	RIGHT-TURN LANE	LEFT-TURN LANE
MT. COMFORT ROAD & CR 700 N/PROPOSED BROADVIEW FARMS SOUTH ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	✓
MT. COMFORT ROAD & 2 ND STREET/PROPOSED MCCORD SQUARE ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	✓	✓
MT. COMFORT ROAD & PROPOSED BROADVIEW FARMS NORTH ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	✓	✓
CR 750 N & MCCORD STREET/PROPOSED BROADVIEW FARMS ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED MCCORD SQUARE EAST ACCESS DRIVE/PROPOSED COLONNADE EAST ACCESS DRIVE (EASTBOUND)	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED MCCORD SQUARE EAST ACCESS DRIVE/PROPOSED COLONNADE EAST ACCESS DRIVE (WESTBOUND)	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED MCCORD SQUARE WEST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED MCCORD SQUARE TOWNHOME ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
BROADWAY & PROPOSED MCCORD SQUARE WEST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	N/A
BROADWAY & PROPOSED MCCORD SQUARE EAST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	✓	✓
SR 234 & PROPOSED MCCORD SQUARE ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	✓

³ INDOT *Driveway Permit Manual*, Indiana Department of Transportation, 2018

CR 700 N & PROPOSED COLONNADE EAST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED COLONNADE WEST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED JACOBI LEGACY FARMS WEST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED JACOBI LEGACY FARMS MAIN ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 750 N & PROPOSED JACOBI LEGACY FARMS EAST ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X
CR 500 W & PROPOSED JACOBI LEGACY FARMS ACCESS DRIVE	Year 2041 Background Traffic Volumes + Proposed Development Traffic Volumes	X	X

✓ = Turn lane warranted; X = Turn lane not warranted; N/A = Not Applicable

It should be noted that even where right-turn lanes are not warranted, the Town of McCordsville Subdivision Control Ordinance requires the installation of right-turn lanes along the public roadway system at access drive locations. Where left-turn lanes are not shown to be warranted, passing blisters may be deemed necessary if right-of-way is available or can be obtained.

The graphs that show the left-turn lane and right-turn lane warrant criteria for the intersection are shown in the **Appendix**.

CAPACITY ANALYSIS

The "efficiency" of an intersection is based on its ability to accommodate the traffic volumes that approach the intersection. It is defined by the Level-of-Service (LOS) of the intersection. The LOS is determined by a series of calculations commonly called a "capacity analysis". Input data into a capacity analysis include traffic volumes, intersection geometry, and number and use of lanes. To determine the LOS at each of the study intersections, a capacity analysis has been made using the recognized computer program *Synchro/SimTraffic*⁴. This program allows intersections to be analyzed and optimized using the capacity calculation methods outlined within the *Highway Capacity Manual (HCM 6th Edition)*⁵. The following list shows the delays related to the levels of service for unsignalized intersections:

⁴ *Synchro/SimTraffic 11*, Trafficware, 2020.

⁵ *Highway Capacity Manual (HCM)*, 6th Edition Transportation Research Board, National Research Council, Washington, DC, 2016.

<u>Level of Service</u>	<u>Control Delay (seconds/vehicle)</u>	
	<u>UNSIGNALIZED</u>	<u>SIGNALIZED</u>
A	Less than or equal to 10	Less than or equal to 10
B	Between 10.1 and 15	Between 10.1 and 20
C	Between 15.1 and 25	Between 20.1 and 35
D	Between 25.1 and 35	Between 35.1 and 55
E	Between 35.1 and 50	Between 55.1 and 80
F	greater than 50	greater than 80

CAPACITY ANALYSIS SCENARIOS

To evaluate the proposed developments' effect on the public street system, a series of traffic volume scenarios were analyzed to determine the adequacy of the existing roadway network. From this analysis, necessary recommendations can be made to improve the public street system so it will accommodate the future traffic volumes. An analysis has been made for the peak hours at each of the study intersections for the following traffic volume scenarios:

Scenario 1: Existing Traffic Volumes – Based on existing peak hour traffic volumes. **Figure 2** is a summary of these traffic volumes.

Scenario 2: Year 2041 Proposed Development Traffic Volumes – Based on the sum of calculated year 2041 background traffic volumes and generated traffic from the proposed developments.

Figure 4 is a summary of these traffic volumes.

The following tables summarize the level of service results at each study intersections. The *Synchro (HCM 6th Edition)* intersection reports illustrating the capacity analysis results are included in the **Appendix**.

TABLE 10 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & CR 700 N/PROPOSED BROADVIEW FARMS SOUTH ACCESS DRIVE (INT 1)

APPROACH	AM PEAK			PM PEAK		
	Scenarios			Scenarios		
	1	2A	2B	1	2A	2B
Northbound Approach	-	A	A	-	A	A
Southbound Approach	A	A	A	A	A	A
Eastbound Approach	-	F	A	-	E	A
Westbound Approach	C	F	A	B	D	A
Intersection	-	-	A	-	-	A

Scenario 2A considers the construction of the eastbound approach with one inbound and two outbound lanes that will stop for Mt. Comfort Road. Analysis considers the construction of an exclusive northbound left-turn lane at the access drive.

Scenario 2B considers the construction of the eastbound approach with one inbound and one outbound lane and considers the intersection as a roundabout.

TABLE 11 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & CR 750 N (INT 2)

APPROACH	AM PEAK			PM PEAK		
	Scenarios			Scenarios		
	1	2A	2B	1	2A	2B
Northbound Approach	A	A	A	A	A	A
Southbound Approach	A	A	A	A	A	A
Eastbound Approach	C	F	A	B	F	A
Westbound Approach	C	F	B	B	F	A
Intersection	-	-	A	-	-	A

Scenario 2A considers existing intersection conditions.

Scenario 2B considers the intersection as a roundabout.

TABLE 12 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & 2ND STREET/PROPOSED MCCORD SQUARE ACCESS DRIVE (INT 3)

APPROACH	AM PEAK			PM PEAK		
	Scenarios			Scenarios		
	1	2A	2B	1	2A	2B
Northbound Approach	A	A	B	A	A	A
Southbound Approach	-	A	A	-	A	A
Eastbound Approach	B	E	B	B	E	B
Westbound Approach	-	E	B	-	E	B
Intersection	-	-	B	-	-	A

Scenario 2A considers the construction of the westbound approach with one inbound and two outbound lanes that will stop for Mt. Comfort Road. Analysis considers the construction of an exclusive northbound right-turn lane and an exclusive southbound left-turn lane at the access drive.

Scenario 2B considers the construction of the westbound approach with one inbound and two outbound lanes. Analysis considers the installation of a traffic signal and the construction of an exclusive northbound left-turn lane and an exclusive southbound left-turn lane.

TABLE 13 – LEVEL OF SERVICE SUMMARY: SR 234 & BROADWAY (INT 4)

APPROACH	AM PEAK		PM PEAK	
	Scenarios		Scenarios	
	1	2	1	2
Northbound Approach	A	A	A	B
Southbound Approach	B	B	A	A
Eastbound Approach	C	C	C	C
Westbound Approach	B	B	B	B
Intersection	A	B	A	B

TABLE 14 – LEVEL OF SERVICE SUMMARY: SR 234 & CR 500 W (INT 5)

APPROACH	AM PEAK			PM PEAK		
	Scenarios			Scenarios		
	1	2A	2B	1	2A	2B
Northbound Approach	B	D	A	B	C	A
Southbound Approach	C	F	A	B	D	A
Eastbound Approach	A	A	A	A	A	A
Westbound Approach	A	A	A	A	A	A
Intersection	-	-	A	-	-	A

Scenario 2A considers existing intersection conditions.

Scenario 2B considers the intersection as a lane roundabout.

TABLE 15 – LEVEL OF SERVICE SUMMARY: CR 750 N & CR 500 W (INT 6)

APPROACH	AM PEAK		PM PEAK	
	Scenarios		Scenarios	
	1	2	1	2
Northbound Left-Turn	A	A	A	A
Eastbound Approach	A	B	A	B

TABLE 16 – LEVEL OF SERVICE SUMMARY: CR 700 N & 500 W (INT 7)

APPROACH	AM PEAK		PM PEAK	
	Scenarios		Scenarios	
	1	2	1	2
Northbound Left-Turn	A	A	A	A
Southbound Left-Turn	A	A	A	A
Eastbound Approach	B	B	A	B
Westbound Approach	A	B	A	B

TABLE 17 – LEVEL OF SERVICE SUMMARY: MT. COMFORT ROAD & PROPOSED BROADVIEW FARMS
NORTH ACCESS DRIVE (INT 8)

APPROACH	AM PEAK		PM PEAK	
	Scenarios		Scenarios	
	2		2	
Northbound Approach	A		A	
Southbound Approach	A		A	
Eastbound Left-Turn	F		E	
Westbound Left-Turn	A		A	

Analysis considers the construction of the eastbound approach with one inbound and two outbound lanes that will stop for Mt. Comfort Road and the construction of an exclusive northbound left-turn lane and an exclusive southbound right-turn lane.

TABLE 18 – LEVEL OF SERVICE SUMMARY: CR 750 N & MCCORD STREET/PROPOSED BROADVIEW FARMS ACCESS DRIVE (INT 9)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Northbound Approach	B	B
Southbound Approach	A	B
Eastbound Left-Turn	A	A
Westbound Left-Turn	A	A

Analysis considers the construction of the northbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 19 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED MCCORD SQUARE EAST ACCESS DRIVE/PROPOSED COLONNADE EAST ACCESS DRIVE (INT 10)

APPROACH	AM PEAK		PM PEAK	
	Scenarios		Scenarios	
	2A	2B	2A	2B
Northbound Approach	B	A	B	A
Southbound Approach	A	A	B	A
Eastbound Approach	A	A	A	A
Westbound Approach	A	A	A	A
Intersection	-	A	-	A

Scenario 2A considers the construction of the northbound and southbound approaches with one inbound and two outbound lanes that will stop for CR 750 N.

Scenario 2B considers the construction of the northbound and southbound approaches with one inbound and one outbound lane. Analysis considers the intersection as a roundabout.

TABLE 20 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED MCCORD SQUARE WEST ACCESS DRIVE (INT 11)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Southbound Approach	B	B
Eastbound Left-Turn	A	A

Analysis considers construction of the southbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 21 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED MCCORD SQUARE TOWNHOME ACCESS DRIVE (INT 12)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Southbound Approach	B	B
Eastbound Left-Turn	A	A

Analysis considers construction of the southbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 22 – LEVEL OF SERVICE SUMMARY: BROADWAY & PROPOSED MCCORD SQUARE WEST
ACCESS DRIVE (INT 13)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Northbound Approach	C	D
Westbound Left-Turn	A	B

TABLE 23 – LEVEL OF SERVICE SUMMARY: BROADWAY & PROPOSED MCCORD SQUARE EAST
ACCESS DRIVE (INT 14)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Northbound Approach	E	F
Westbound Left-Turn	A	B

Analysis considers construction of the northbound approach with one inbound and two outbound lanes that will stop for Broadway. Analysis considers the construction of an exclusive eastbound right-turn lane and an exclusive westbound left-turn lane along Broadway at the access drive.

TABLE 24 – LEVEL OF SERVICE SUMMARY: SR 234 & PROPOSED MCCORD SQUARE ACCESS DRIVE
(INT 15)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Northbound Approach	B	B
Southbound Approach	A	A
Eastbound Left-Turn	A	A
Westbound Left-Turn	A	A

Analysis considers the construction of the northbound approach with one inbound and two outbound lanes that will stop for SR 234 and the construction of an exclusive westbound left-turn lane along SR 234 at the access drive.

TABLE 25 – LEVEL OF SERVICE SUMMARY: CR 700 N & PROPOSED COLONNADE ACCESS DRIVE
(INT 16)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Southbound Approach	A	A
Eastbound Left-Turn	A	A

Analysis considers the construction of the southbound approach with one inbound and two outbound lanes that will stop for CR 700 N.

TABLE 26 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED COLONNADE WEST ACCESS DRIVE (INT 17)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Northbound Approach	B	B
Westbound Left-Turn	A	A

Analysis considers the construction of the northbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 27 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED JACOBI LEGACY FARMS WEST ACCESS DRIVE (INT 18)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Southbound Approach	A	A
Eastbound Left-Turn	A	A

Analysis considers the construction of the southbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 28 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED JACOBI LEGACY FARMS MAIN ACCESS DRIVE (INT 19)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Southbound Approach	A	A
Eastbound Left-Turn	A	A

Analysis considers the construction of the southbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 29 – LEVEL OF SERVICE SUMMARY: CR 750 N & PROPOSED JACOBI LEGACY FARMS EAST ACCESS DRIVE (INT 20)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Southbound Approach	A	A
Eastbound Left-Turn	A	A

Analysis considers the construction of the southbound approach with one inbound and two outbound lanes that will stop for CR 750 N.

TABLE 30 – LEVEL OF SERVICE SUMMARY: CR 500 W & PROPOSED JACOBI LEGACY FARMS
ACCESS DRIVE (INT 21)

APPROACH	AM PEAK	PM PEAK
	Scenarios	Scenarios
	2	2
Northbound Left-Turn	A	A
Eastbound Approach	B	B

Analysis considers the construction of the eastbound approach with one inbound and two outbound lanes that will stop for CR 500 W.

TABLE 31 – LEVEL OF SERVICE SUMMARY: MCCORD SQUARE ACCESS DRIVE & JACOBI LEGACY
FARMS ACCESS DRIVE (INT 22)

APPROACH	AM PEAK		PM PEAK	
	Scenarios		Scenarios	
	2A	2B	2A	2B
Northbound Approach	A	A	A	A
Southbound Approach	A	A	A	A
Eastbound Approach	A	A	A	A
Westbound Approach	A	A	A	A
Intersection	-	A	-	A

Scenario 2A considers the intersection as a two-way stop-controlled intersection with the east/west approaches stopping for the north/south approaches.

Scenario 2B considers the intersection as a roundabout.

RECOMMENDATIONS

The recommendations that follow are based on existing traffic volume data, trip generation, assignment and distribution of generated traffic, turn lane analysis, capacity analyses/level of service results, and a field review conducted at the site. The following recommendations are formulated to ensure that the roadway system will accommodate the increased traffic volumes from the site.

MT. COMFORT ROAD & CR 700 N/PROPOSED BROADVIEW FARMS SOUTH ACCESS DRIVE (INT 1)

- Construction of the eastbound approach with one inbound lane and one outbound lane.
- Conversion of the intersection to a dual-lane roundabout with two entering/exiting lanes on the northbound/southbound approaches and one entering/exiting lane on the eastbound/westbound approaches.

MT. COMFORT ROAD & CR 750 N (INT 2)

- Conversion of the intersection to a dual-lane roundabout with two entering/exiting lanes on the northbound/southbound approaches and one entering/exiting lane on the eastbound/westbound approaches.

MT. COMFORT ROAD & 2ND STREET/PROPOSED MCCORD SQUARE ACCESS DRIVE (INT 3)

- Installation of a traffic signal.
- Construction of the westbound approach with one inbound and two outbound lanes.
- Construction of an exclusive northbound left-turn lane and an exclusive southbound left-turn lane.

SR 234 & BROADWAY (INT 4)

- There are no recommended improvements at this intersection.

SR 234 & CR 500 W (INT 5)

- Conversion of the intersection to a single lane roundabout with one entering/exiting lane on each approach.
 - INDOT already has plans to make this improvement.

CR 750 N & CR 500 W (INT 6)

- There are no recommended improvements at this intersection.

CR 700 N & CR 500 W (INT 7)

- There are no recommended improvements at this intersection.

MT. COMFORT ROAD & PROPOSED BROADVIEW FARMS NORTH ACCESS DRIVE (INT 8)

- Construction of the eastbound approach with one inbound lane and two outbound lanes.
- Construction of an exclusive northbound left-turn lane and an exclusive southbound right-turn lane along Mt. Comfort Road at this location.
- The intersection should be stop controlled with the access drive stopping for Mt. Comfort Road.

CR 750 N & MCCORD STREET/PROPOSED BROADVIEW FARMS ACCESS DRIVE (INT 9)

- Construction of the northbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.

CR 750 N & PROPOSED McCORD SQUARE EAST ACCESS DRIVE/COLONNADE EAST ACCESS DRIVE
(INT 10)

- Construction of the northbound approach and southbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lanes along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.

CR 750 N & PROPOSED McCORD SQUARE WEST ACCESS DRIVE (INT 11)

- Construction of the southbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

CR 750 N & PROPOSED McCORD SQUARE TOWNHOME ACCESS DRIVE (INT 12)

- Construction of the southbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

BROADWAY & PROPOSED McCORD SQUARE WEST ACCESS DRIVE (INT 13)

- Construction of the northbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for Broadway.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.

BROADWAY & PROPOSED McCORD SQUARE EAST ACCESS DRIVE (INT 14)

- Construction of the northbound approach with one inbound lane and two outbound lanes.
- Construction of an exclusive westbound left-turn lane and an exclusive westbound right-turn lane along Broadway at this location.
- The intersection should be stop controlled with the access drive stopping for Broadway.

SR 234 & PROPOSED MCCORD SQUARE ACCESS DRIVE (INT 15)

- Construction of the northbound approach with one inbound lane and two outbound lanes.
- Construction of an exclusive westbound left-turn lane along SR 234 at the access drive location.
- The intersection should be stop controlled with the access drive stopping for SR 234.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.

CR 700 N & PROPOSED COLONNADE ACCESS DRIVE (INT 16)

- Construction of the southbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 700 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

CR 750 N & PROPOSED COLONNADE WEST ACCESS DRIVE (INT 17)

- Construction of the northbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

CR 750 N & PROPOSED JACOBI LEGACY FARMS WEST ACCESS DRIVE (INT 18)

- Construction of the southbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

CR 750 N & PROPOSED JACOBI LEGACY FARMS MAIN ACCESS DRIVE (INT 19)

- Construction of the southbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

CR 750 N & PROPOSED JACOBI LEGACY FARMS EAST ACCESS DRIVE (INT 20)

- Construction of the southbound approach with one inbound lane and one outbound lane.
- The intersection should be stop controlled with the access drive stopping for CR 750 N.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

CR 500 W & PROPOSED JACOBI LEGACY FARMS ACCESS DRIVE (INT 21)


- Construction of the northbound approach with one inbound lane and two outbound lanes.
- The intersection should be stop controlled with the access drive stopping for CR 500 W.
- While not warranted, the installation of a right-turn lane along the public roadway system is required by the Town of McCordsville Subdivision Control Ordinance.
- A passing blister may be deemed necessary if right-of-way is available or can be obtained.

MCCORD SQUARE ACCESS DRIVE & JACOBI LEGACY FARMS ACCESS DRIVE (INT 22)

- Construction of all approaches with at least one inbound lane and one outbound lane.
- The intersection should be stop controlled with the eastbound and westbound approaches stopping for the northbound and southbound approaches.

TRAFFIC IMPACT STUDY

APPENDIX



Transportation & Site Engineering

Creating Order Since 1966

***8365 Keystone Crossing Boulevard, Suite 201
Indianapolis, IN 46240
Phone: (317) 202-0864 Fax: (317) 202-0908***

ADDITIONAL FIGURES

DRAFT





FIGURE 2

YEAR 2041 BACKGROUND TRAFFIC VOLUMES

LEGEND


- XX = A.M. PEAK HOUR
- (XX) = P.M. PEAK HOUR
- * = NEGLIGIBLE

**TRAFFIC IMPACT STUDY
TOWN OF MCCORDSVILLE
MCCORDSVILLE, IN**

TURN LANE WARRANT ANALYSIS


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	453	Advancing Volume (Va)	569
Opposing Volume (Vo)	664	Opposing Volume (Vo)	602
Left-Turn Volume	4	Left-Turn Volume	14
% Left-Turn	1%	% Left-Turn	2%
WARRANTED?	YES	WARRANTED?	YES



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	11	No
	Total Volume	664	
PM	RT Volume	37	No
	Total Volume	602	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	562	Advancing Volume (Va)	693
Opposing Volume (Vo)	674	Opposing Volume (Vo)	596
Left-Turn Volume	68	Left-Turn Volume	86
% Left-Turn	12%	% Left-Turn	12%
WARRANTED?	YES	WARRANTED?	YES



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	44	YES
	Total Volume	674	
PM	RT Volume	54	YES
	Total Volume	596	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	648	Advancing Volume (Va)	599
Opposing Volume (Vo)	651	Opposing Volume (Vo)	675
Left-Turn Volume	6	Left-Turn Volume	19
% Left-Turn	1%	% Left-Turn	3%
WARRANTED?	YES	WARRANTED?	YES



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	19	NO
	Total Volume	651	
PM	RT Volume	70	YES
	Total Volume	675	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	260	Advancing Volume (Va)	198
Opposing Volume (Vo)	187	Opposing Volume (Vo)	261
Left-Turn Volume	11	Left-Turn Volume	29
% Left-Turn	4%	% Left-Turn	15%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	5	NO
	Total Volume	187	
PM	RT Volume	16	NO
	Total Volume	261	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	169	Advancing Volume (Va)	128
Opposing Volume (Vo)	120	Opposing Volume (Vo)	223
Left-Turn Volume	2	Left-Turn Volume	8
% Left-Turn	1%	% Left-Turn	6%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	3	NO
	Total Volume	120	
PM	RT Volume	10	NO
	Total Volume	223	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	120	Advancing Volume (Va)	223
Opposing Volume (Vo)	169	Opposing Volume (Vo)	128
Left-Turn Volume	15	Left-Turn Volume	36
% Left-Turn	13%	% Left-Turn	16%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	5	NO
	Total Volume	169	
PM	RT Volume	5	NO
	Total Volume	128	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
45	800	297	233	208	182	160	139	117	95
	600	380	283	246	210	198	185	172	160
	400	470	350	304	258	243	228	212	197
	200	595	435	380	325	306	288	269	250
	100	668	480	421	363	340	318	295	272

INPUT AM		INPUT PM	
Advancing Volume (Va)	158	Advancing Volume (Va)	293
Opposing Volume (Vo)	258	Opposing Volume (Vo)	177
Left-Turn Volume	39	Left-Turn Volume	46
% Left-Turn	25%	% Left-Turn	16%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	14	NO
	Total Volume	259	
PM	RT Volume	16	NO
	Total Volume	177	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
45	800	297	233	208	182	160	139	117	95
	600	380	283	246	210	198	185	172	160
	400	470	350	304	258	243	228	212	197
	200	595	435	380	325	306	288	269	250
	100	668	480	421	363	340	318	295	272

INPUT AM		INPUT PM	
Advancing Volume (Va)	158	Advancing Volume (Va)	299
Opposing Volume (Vo)	278	Opposing Volume (Vo)	216
Left-Turn Volume	4	Left-Turn Volume	8
% Left-Turn	3%	% Left-Turn	3%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	1	No
	Total Volume	278	
PM	RT Volume	3	No
	Total Volume	216	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Total Volume	RT Volume
0	90
500	90
1200	40
1600	40

Time	Input		Met?
AM	RT Volume	5	NO
	Total Volume	699	
PM	RT Volume	18	NO
	Total Volume	136	




Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	685	Advancing Volume (Va)	715
Opposing Volume (Vo)	708	Opposing Volume (Vo)	1210
Left-Turn Volume	46	Left-Turn Volume	76
% Left-Turn	7%	% Left-Turn	11%
WARRANTED?	YES	WARRANTED?	YES




Total Volume	RT Volume
0	90
500	90
1200	40
1600	40

Time	Input		Met?
AM	RT Volume	82	YES
	Total Volume	708	
PM	RT Volume	131	YES
	Total Volume	1210	




Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
55	800	255	190	168	145	135	125	115	105
	600	320	235	206	178	167	155	143	131
	400	398	295	258	220	206	193	179	165
	200	500	365	320	275	259	243	226	210
	100	560	408	356	305	286	268	249	230

INPUT AM		INPUT PM	
Advancing Volume (Va)	306	Advancing Volume (Va)	319
Opposing Volume (Vo)	289	Opposing Volume (Vo)	247
Left-Turn Volume	31	Left-Turn Volume	43
% Left-Turn	10%	% Left-Turn	13%
WARRANTED?	NO	WARRANTED?	YES



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	6	No
	Total Volume	289	
PM	RT Volume	14	No
	Total Volume	247	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
45	800	297	233	208	182	160	139	117	95
	600	380	283	246	210	198	185	172	160
	400	470	350	304	258	243	228	212	197
	200	595	435	380	325	306	288	269	250
	100	668	480	421	363	340	318	295	272

INPUT AM		INPUT PM	
Advancing Volume (Va)	49	Advancing Volume (Va)	95
Opposing Volume (Vo)	40	Opposing Volume (Vo)	56
Left-Turn Volume	18	Left-Turn Volume	61
% Left-Turn	37%	% Left-Turn	64%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	6	No
	Total Volume	40	
PM	RT Volume	21	No
	Total Volume	56	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
45	800	297	233	208	182	160	139	117	95
	600	380	283	246	210	198	185	172	160
	400	470	350	304	258	243	228	212	197
	200	595	435	380	325	306	288	269	250
	100	668	480	421	363	340	318	295	272

INPUT AM		INPUT PM	
Advancing Volume (Va)	202	Advancing Volume (Va)	145
Opposing Volume (Vo)	129	Opposing Volume (Vo)	263
Left-Turn Volume	1	Left-Turn Volume	4
% Left-Turn	0%	% Left-Turn	3%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	13	No
	Total Volume	129	
PM	RT Volume	43	No
	Total Volume	263	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
40	800	313	256	228	199	171	142	113	84
	600	410	305	265	225	213	200	187	175
	400	510	380	328	275	260	245	230	215
	200	640	470	410	350	328	305	282	260
	100	720	515	453	390	365	340	315	290

INPUT AM		INPUT PM	
Advancing Volume (Va)	111	Advancing Volume (Va)	184
Opposing Volume (Vo)	127	Opposing Volume (Vo)	108
Left-Turn Volume	14	Left-Turn Volume	47
% Left-Turn	13%	% Left-Turn	26%
WARRANTED?	NO	WARRANTED?	NO




Total Volume	RT Volume
0	120
600	40
700	40

Time	Input		Met?
AM	RT Volume	2	No
	Total Volume	127	
PM	RT Volume	7	No
	Total Volume	108	




Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
45	800	297	233	208	182	160	139	117	95
	600	380	283	246	210	198	185	172	160
	400	470	350	304	258	243	228	212	197
	200	595	435	380	325	306	288	269	250
	100	668	480	421	363	340	318	295	272

INPUT AM		INPUT PM	
Advancing Volume (Va)	100	Advancing Volume (Va)	140
Opposing Volume (Vo)	85	Opposing Volume (Vo)	92
Left-Turn Volume	14	Left-Turn Volume	49
% Left-Turn	14%	% Left-Turn	35%
WARRANTED?	NO	WARRANTED?	NO




Total Volume	RT Volume
0	120
600	40
700	40

Time	Input		Met?
AM	RT Volume	4	No
	Total Volume	85	
PM	RT Volume	12	No
	Total Volume	92	




Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
45	800	297	233	208	182	160	139	117	95
	600	380	283	246	210	198	185	172	160
	400	470	350	304	258	243	228	212	197
	200	595	435	380	325	306	288	269	250
	100	668	480	421	363	340	318	295	272

INPUT AM		INPUT PM	
Advancing Volume (Va)	97	Advancing Volume (Va)	99
Opposing Volume (Vo)	68	Opposing Volume (Vo)	103
Left-Turn Volume	7	Left-Turn Volume	21
% Left-Turn	7%	% Left-Turn	21%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40


Time	Input		Met?
AM	RT Volume	4	No
	Total Volume	68	
PM	RT Volume	15	No
	Total Volume	103	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.


Operating Speed (mph)	Opposing Volume (veh/h)	Advancing Volume (veh/h)							
		5% Left Turns	10% Left Turns	15% Left Turns	20% Left Turns	25% Left Turns	30% Left Turns	35% Left Turns	40% Left Turns
50	800	280	210	188	165	150	135	120	105
	600	350	260	228	195	183	170	157	145
	400	430	320	280	240	225	210	195	180
	200	550	400	350	300	285	270	255	240
	100	615	445	390	335	315	295	275	255

INPUT AM		INPUT PM	
Advancing Volume (Va)	186	Advancing Volume (Va)	159
Opposing Volume (Vo)	125	Opposing Volume (Vo)	161
Left-Turn Volume	8	Left-Turn Volume	20
% Left-Turn	4%	% Left-Turn	13%
WARRANTED?	NO	WARRANTED?	NO



Total Volume	RT Volume
0	120
600	40
700	40

Time	Input		Met?
AM	RT Volume	11	No
	Total Volume	125	
PM	RT Volume	31	No
	Total Volume	161	



NOTE : For highways with a design speed below 80 km/h (50 mph) with a DHV < 300 and where right turns > 40, an adjustment should be used. To read the vertical axis of the chart, subtract 20 from the actual number of right turns.

***MT. COMFORT ROAD & CR 700 N/PROPOSED
BROADVIEW FARMS SOUTH ACCESS DRIVE***

***TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS***

Intersection

Int Delay, s/veh 2.2

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	9	14	266	80	164	320
Future Vol, veh/h	9	14	266	80	164	320
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	210	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	84	84	84	84	84	84
Heavy Vehicles, %	5	5	5	5	5	5
Mvmt Flow	11	17	317	95	195	381

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	1136	365	0
Stage 1	365	-	-
Stage 2	771	-	-
Critical Hdwy	6.45	6.25	-
Critical Hdwy Stg 1	5.45	-	-
Critical Hdwy Stg 2	5.45	-	-
Follow-up Hdwy	3.545	3.345	-
Pot Cap-1 Maneuver	220	673	-
Stage 1	696	-	-
Stage 2	451	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	182	673	-
Mov Cap-2 Maneuver	182	-	-
Stage 1	696	-	-
Stage 2	373	-	-

Approach	WB	NB	SB
HCM Control Delay, s	17	0	3
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	327	1131
HCM Lane V/C Ratio	-	-	0.084	0.173
HCM Control Delay (s)	-	-	17	8.8
HCM Lane LOS	-	-	C	A
HCM 95th %tile Q(veh)	-	-	0.3	0.6

Intersection

Int Delay, s/veh 0.3

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W	R	T	R	T	T
Traffic Vol, veh/h	6	9	378	7	8	381
Future Vol, veh/h	6	9	378	7	8	381
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	210	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	91	91	91	91	91	91
Heavy Vehicles, %	1	1	1	1	1	1
Mvmt Flow	7	10	415	8	9	419

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	856	419	0
Stage 1	419	-	-
Stage 2	437	-	-
Critical Hdwy	6.41	6.21	-
Critical Hdwy Stg 1	5.41	-	-
Critical Hdwy Stg 2	5.41	-	-
Follow-up Hdwy	3.509	3.309	-
Pot Cap-1 Maneuver	329	636	-
Stage 1	666	-	-
Stage 2	653	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	326	636	-
Mov Cap-2 Maneuver	326	-	-
Stage 1	666	-	-
Stage 2	648	-	-

Approach	WB	NB	SB
HCM Control Delay, s	13.1	0	0.2
HCM LOS	B		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	461	1142
HCM Lane V/C Ratio	-	-	0.036	0.008
HCM Control Delay (s)	-	-	13.1	8.2
HCM Lane LOS	-	-	B	A
HCM 95th %tile Q(veh)	-	-	0.1	0

Intersection

Int Delay, s/veh 8.4

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	37	9	11	25	4	39	4	356	93	203	450	11
Future Vol, veh/h	37	9	11	25	4	39	4	356	93	203	450	11
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	0	-	-	-	-	-	100	-	-	210	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	84	92	84	92	84	84	84	84	92
Heavy Vehicles, %	2	2	2	5	2	5	2	5	5	5	5	2
Mvmt Flow	40	10	12	30	4	46	4	424	111	242	536	12

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	1539	1569	542	1525	1520	480	548	0	0	535	0	0
Stage 1	1026	1026	-	488	488	-	-	-	-	-	-	-
Stage 2	513	543	-	1037	1032	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.15	6.52	6.25	4.12	-	-	4.15	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.15	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.15	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.545	4.018	3.345	2.218	-	-	2.245	-	-
Pot Cap-1 Maneuver	94	111	540	95	119	580	1021	-	-	1018	-	-
Stage 1	283	312	-	556	550	-	-	-	-	-	-	-
Stage 2	544	520	-	276	310	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	68	84	540	69	90	580	1021	-	-	1018	-	-
Mov Cap-2 Maneuver	68	84	-	69	90	-	-	-	-	-	-	-
Stage 1	282	238	-	554	548	-	-	-	-	-	-	-
Stage 2	495	518	-	197	236	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	86.5	57.8	0.1	2.9
HCM LOS	F	F		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	EBLn2	WBLn1	SBL	SBT	SBR
Capacity (veh/h)	1021	-	-	68	157	144	1018	-	-
HCM Lane V/C Ratio	0.004	-	-	0.591	0.138	0.559	0.237	-	-
HCM Control Delay (s)	8.5	-	-	116.1	31.6	57.8	9.6	-	-
HCM Lane LOS	A	-	-	F	D	F	A	-	-
HCM 95th %tile Q(veh)	0	-	-	2.5	0.5	2.8	0.9	-	-

Intersection

Int Delay, s/veh 3.2

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	23	6	7	17	13	31	14	529	26	59	506	37
Future Vol, veh/h	23	6	7	17	13	31	14	529	26	59	506	37
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	0	-	-	-	-	-	100	-	-	210	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	91	92	91	92	91	91	91	91	92
Heavy Vehicles, %	2	2	2	1	2	1	2	1	1	1	1	2
Mvmt Flow	25	7	8	19	14	34	15	581	29	65	556	40

Major/Minor	Minor2		Minor1		Major1		Major2		Major2		Major2	
Conflicting Flow All	1356	1346	576	1340	1352	596	596	0	0	610	0	0
Stage 1	706	706	-	626	626	-	-	-	-	-	-	-
Stage 2	650	640	-	714	726	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.11	6.52	6.21	4.12	-	-	4.11	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.11	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.11	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.509	4.018	3.309	2.218	-	-	2.209	-	-
Pot Cap-1 Maneuver	126	151	517	130	150	505	980	-	-	974	-	-
Stage 1	427	439	-	474	477	-	-	-	-	-	-	-
Stage 2	458	470	-	424	430	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	102	139	517	116	138	505	980	-	-	974	-	-
Mov Cap-2 Maneuver	102	139	-	116	138	-	-	-	-	-	-	-
Stage 1	421	410	-	467	470	-	-	-	-	-	-	-
Stage 2	408	463	-	384	401	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	40.7	31.4	0.2	0.9
HCM LOS	E	D		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	EBLn2	WBLn1	SBL	SBT	SBR
Capacity (veh/h)	980	-	-	102	229	202	974	-	-
HCM Lane V/C Ratio	0.016	-	-	0.245	0.062	0.331	0.067	-	-
HCM Control Delay (s)	8.7	-	-	51.4	21.8	31.4	9	-	-
HCM Lane LOS	A	-	-	F	C	D	A	-	-
HCM 95th %tile Q(veh)	0	-	-	0.9	0.2	1.4	0.2	-	-

HCM 6th Roundabout
1: Mt. Comfort Rd & Broadview Farms South Access/CR 700 N

Background + Proposed AM

Mitigated

Intersection						
Intersection Delay, s/veh	5.8					
Intersection LOS	A					
Approach	EB	WB	NB	SB		
Entry Lanes	1	1	2	2		
Conflicting Circle Lanes	2	2	2	2		
Adj Approach Flow, veh/h	62	80	539	790		
Demand Flow Rate, veh/h	63	84	566	829		
Vehicles Circulating, veh/h	848	490	305	39		
Vehicles Exiting, veh/h	20	381	606	534		
Ped Vol Crossing Leg, #/h	0	0	0	0		
Ped Cap Adj	1.000	1.000	1.000	1.000		
Approach Delay, s/veh	6.3	4.9	6.2	5.6		
Approach LOS	A	A	A	A		
Lane	Left	Left	Left	Right	Left	Right
Designated Moves	LTR	LTR	LT	TR	LT	TR
Assumed Moves	LTR	LTR	LT	TR	LT	TR
RT Channelized						
Lane Util	1.000	1.000	0.470	0.530	0.470	0.530
Follow-Up Headway, s	2.535	2.535	2.667	2.535	2.667	2.535
Critical Headway, s	4.328	4.328	4.645	4.328	4.645	4.328
Entry Flow, veh/h	63	84	266	300	390	439
Cap Entry Lane, veh/h	691	936	1020	1096	1302	1374
Entry HV Adj Factor	0.981	0.951	0.952	0.952	0.952	0.954
Flow Entry, veh/h	62	80	253	286	371	419
Cap Entry, veh/h	678	891	971	1043	1240	1311
V/C Ratio	0.091	0.090	0.261	0.274	0.299	0.320
Control Delay, s/veh	6.3	4.9	6.3	6.1	5.6	5.6
LOS	A	A	A	A	A	A
95th %tile Queue, veh	0	0	1	1	1	1

Intersection						
Intersection Delay, s/veh	5.0					
Intersection LOS	A					
Approach	EB	WB	NB	SB		
Entry Lanes	1	1	2	2		
Conflicting Circle Lanes	2	2	2	2		
Adj Approach Flow, veh/h	40	67	625	661		
Demand Flow Rate, veh/h	41	67	631	669		
Vehicles Circulating, veh/h	647	627	98	48		
Vehicles Exiting, veh/h	70	102	589	646		
Ped Vol Crossing Leg, #/h	0	0	0	0		
Ped Cap Adj	1.000	1.000	1.000	1.000		
Approach Delay, s/veh	5.0	5.1	5.0	4.9		
Approach LOS	A	A	A	A		
Lane	Left	Left	Left	Right	Left	Right
Designated Moves	LTR	LTR	LT	TR	LT	TR
Assumed Moves	LTR	LTR	LT	TR	LT	TR
RT Channelized						
Lane Util	1.000	1.000	0.471	0.529	0.469	0.531
Follow-Up Headway, s	2.535	2.535	2.667	2.535	2.667	2.535
Critical Headway, s	4.328	4.328	4.645	4.328	4.645	4.328
Entry Flow, veh/h	41	67	297	334	314	355
Cap Entry Lane, veh/h	819	833	1233	1307	1292	1363
Entry HV Adj Factor	0.972	0.996	0.989	0.992	0.990	0.987
Flow Entry, veh/h	40	67	294	331	311	351
Cap Entry, veh/h	797	830	1220	1296	1279	1346
V/C Ratio	0.050	0.080	0.241	0.256	0.243	0.260
Control Delay, s/veh	5.0	5.1	5.1	5.0	4.9	4.9
LOS	A	A	A	A	A	A
95th %tile Queue, veh	0	0	1	1	1	1

MT. COMFORT ROAD & CR 750 N

TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	2.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	0	13	84	1	9	10	66	391	19	6	387	6
Future Vol, veh/h	0	13	84	1	9	10	66	391	19	6	387	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	85	85	85	85	85	85
Heavy Vehicles, %	4	4	4	4	4	4	4	4	4	4	4	4
Mvmt Flow	0	15	99	1	11	12	78	460	22	7	455	7
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	1112	1111	459	1157	1103	471	462	0	0	482	0	0
Stage 1	473	473	-	627	627	-	-	-	-	-	-	-
Stage 2	639	638	-	530	476	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.14	6.54	6.24	4.14	-	-	4.14	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.536	4.036	3.336	2.236	-	-	2.236	-	-
Pot Cap-1 Maneuver	184	207	598	172	210	589	1089	-	-	1070	-	-
Stage 1	568	555	-	468	473	-	-	-	-	-	-	-
Stage 2	461	468	-	529	553	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	159	185	598	124	188	589	1089	-	-	1070	-	-
Mov Cap-2 Maneuver	159	185	-	124	188	-	-	-	-	-	-	-
Stage 1	512	550	-	422	427	-	-	-	-	-	-	-
Stage 2	397	422	-	425	548	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	15.4		19.4			1.2			0.1			
HCM LOS	C		C									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1089	-	-	460	274	1070	-	-				
HCM Lane V/C Ratio	0.071	-	-	0.248	0.086	0.007	-	-				
HCM Control Delay (s)	8.6	0	-	15.4	19.4	8.4	0	-				
HCM Lane LOS	A	A	-	C	C	A	A	-				
HCM 95th %tile Q(veh)	0.2	-	-	1	0.3	0	-	-				

Intersection												
Int Delay, s/veh	1.5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	3	11	50	0	3	2	30	367	4	7	353	13
Future Vol, veh/h	3	11	50	0	3	2	30	367	4	7	353	13
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	95	95	95	95	95	95	95	95	95	95	95	95
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	3	12	53	0	3	2	32	386	4	7	372	14
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	848	847	379	878	852	388	386	0	0	390	0	0
Stage 1	393	393	-	452	452	-	-	-	-	-	-	-
Stage 2	455	454	-	426	400	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	281	299	668	268	297	660	1172	-	-	1169	-	-
Stage 1	632	606	-	587	570	-	-	-	-	-	-	-
Stage 2	585	569	-	606	602	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	269	286	668	232	284	660	1172	-	-	1169	-	-
Mov Cap-2 Maneuver	269	286	-	232	284	-	-	-	-	-	-	-
Stage 1	610	601	-	566	550	-	-	-	-	-	-	-
Stage 2	559	549	-	543	597	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	13.1		14.9			0.6			0.2			
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1172	-	-	514	368	1169	-	-				
HCM Lane V/C Ratio	0.027	-	-	0.131	0.014	0.006	-	-				
HCM Control Delay (s)	8.2	0	-	13.1	14.9	8.1	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0.1	-	-	0.4	0	0	-	-				

Intersection												
Int Delay, s/veh	561.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	34	67	110	61	134	90	92	492	64	33	480	35
Future Vol, veh/h	34	67	110	61	134	90	92	492	64	33	480	35
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	85	85	85	85	85	85	85	85	85	85	85	85
Heavy Vehicles, %	4	4	4	4	4	4	4	4	4	4	4	4
Mvmt Flow	40	79	129	72	158	106	108	579	75	39	565	41
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	1629	1534	586	1601	1517	617	606	0	0	654	0	0
Stage 1	664	664	-	833	833	-	-	-	-	-	-	-
Stage 2	965	870	-	768	684	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.14	6.54	6.24	4.14	-	-	4.14	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.536	4.036	3.336	2.236	-	-	2.236	-	-
Pot Cap-1 Maneuver	81	115	506	84	~118	486	962	-	-	923	-	-
Stage 1	447	455	-	360	381	-	-	-	-	-	-	-
Stage 2	304	366	-	391	446	-	-	-	-	-	-	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	-	88	506	~12	~91	486	962	-	-	923	-	-
Mov Cap-2 Maneuver	-	88	-	~12	~91	-	-	-	-	-	-	-
Stage 1	367	426	-	296	313	-	-	-	-	-	-	-
Stage 2	97	300	-	222	417	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s			\$ 3328.3			1.3			0.5			
HCM LOS	-		F									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	962	-	-	-	42	923	-	-				
HCM Lane V/C Ratio	0.113	-	-	-	7.983	0.042	-	-				
HCM Control Delay (s)	9.2	0	-	\$ 3328.3	9.1	0	-					
HCM Lane LOS	A	A	-	F	A	A	-					
HCM 95th %tile Q(veh)	0.4	-	-	-	39.8	0.1	-	-				
Notes												
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined			*: All major volume in platoon				

Intersection													
Int Delay, s/veh	0.7												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR	
Lane Configurations		↕			↕			↕			↕		
Traffic Vol, veh/h	31	128	102	65	100	51	48	494	77	93	509	48	
Future Vol, veh/h	31	128	102	65	100	51	48	494	77	93	509	48	
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0	
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free	
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None	
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-	
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-	
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-	
Peak Hour Factor	95	95	95	95	95	95	95	95	95	95	95	95	
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2	
Mvmt Flow	33	135	107	68	105	54	51	520	81	98	536	51	
Major/Minor	Minor2		Minor1			Major1			Major2				
Conflicting Flow All	1500	1461	562	1542	1446	561	587	0	0	601	0	0	
Stage 1	758	758	-	663	663	-	-	-	-	-	-	-	
Stage 2	742	703	-	879	783	-	-	-	-	-	-	-	
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-	
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-	
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-	
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-	
Pot Cap-1 Maneuver	100	~ 129	526	94	132	527	988	-	-	976	-	-	
Stage 1	399	415	-	450	459	-	-	-	-	-	-	-	
Stage 2	408	440	-	342	404	-	-	-	-	-	-	-	
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-	
Mov Cap-1 Maneuver	-	~ 101	526	-	~ 103	527	988	-	-	976	-	-	
Mov Cap-2 Maneuver	-	~ 101	-	-	~ 103	-	-	-	-	-	-	-	
Stage 1	367	353	-	414	423	-	-	-	-	-	-	-	
Stage 2	254	405	-	143	343	-	-	-	-	-	-	-	
Approach	EB		WB			NB			SB				
HCM Control Delay, s							0.7			1.3			
HCM LOS	-		-										
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	988	-	-	-	-	976	-	-					
HCM Lane V/C Ratio	0.051	-	-	-	-	0.1	-	-					
HCM Control Delay (s)	8.8	0	-	-	-	9.1	0	-					
HCM Lane LOS	A	A	-	-	-	A	A	-					
HCM 95th %tile Q(veh)	0.2	-	-	-	-	0.3	-	-					
Notes													
~: Volume exceeds capacity		\$: Delay exceeds 300s			+: Computation Not Defined			*: All major volume in platoon					

Intersection						
Intersection Delay, s/veh 7.8						
Intersection LOS A						
Approach	EB	WB	NB	SB		
Entry Lanes	1	1	2	2		
Conflicting Circle Lanes	2	2	2	2		
Adj Approach Flow, veh/h	248	336	762	645		
Demand Flow Rate, veh/h	258	349	792	672		
Vehicles Circulating, veh/h	704	756	165	351		
Vehicles Exiting, veh/h	319	201	797	754		
Ped Vol Crossing Leg, #/h	0	0	0	0		
Ped Cap Adj	1.000	1.000	1.000	1.000		
Approach Delay, s/veh	8.8	11.7	6.3	7.2		
Approach LOS	A	B	A	A		
Lane	Left	Left	Left	Right	Left	Right
Designated Moves	LTR	LTR	LT	TR	LT	TR
Assumed Moves	LTR	LTR	LT	TR	LT	TR
RT Channelized						
Lane Util	1.000	1.000	0.470	0.530	0.470	0.530
Follow-Up Headway, s	2.535	2.535	2.667	2.535	2.667	2.535
Critical Headway, s	4.328	4.328	4.645	4.328	4.645	4.328
Entry Flow, veh/h	258	349	372	420	316	356
Cap Entry Lane, veh/h	781	747	1160	1234	977	1054
Entry HV Adj Factor	0.961	0.962	0.963	0.961	0.960	0.961
Flow Entry, veh/h	248	336	358	404	303	342
Cap Entry, veh/h	750	718	1116	1187	938	1012
V/C Ratio	0.331	0.467	0.321	0.340	0.323	0.338
Control Delay, s/veh	8.8	11.7	6.3	6.3	7.3	7.0
LOS	A	B	A	A	A	A
95th %tile Queue, veh	1	3	1	2	1	2

Intersection						
Intersection Delay, s/veh 6.9						
Intersection LOS A						
Approach	EB	WB	NB		SB	
Entry Lanes	1	1	2		2	
Conflicting Circle Lanes	2	2	2		2	
Adj Approach Flow, veh/h	275	227	652		685	
Demand Flow Rate, veh/h	281	231	665		699	
Vehicles Circulating, veh/h	716	616	272		228	
Vehicles Exiting, veh/h	211	321	725		619	
Ped Vol Crossing Leg, #/h	0	0	0		0	
Ped Cap Adj	1.000	1.000	1.000		1.000	
Approach Delay, s/veh	9.3	7.4	6.4		6.2	
Approach LOS	A	A	A		A	
Lane	Left	Left	Left	Right	Left	Right
Designated Moves	LTR	LTR	LT	TR	LT	TR
Assumed Moves	LTR	LTR	LT	TR	LT	TR
RT Channelized						
Lane Util	1.000	1.000	0.471	0.529	0.471	0.529
Follow-Up Headway, s	2.535	2.535	2.667	2.535	2.667	2.535
Critical Headway, s	4.328	4.328	4.645	4.328	4.645	4.328
Entry Flow, veh/h	281	231	313	352	329	370
Cap Entry Lane, veh/h	773	841	1051	1127	1094	1170
Entry HV Adj Factor	0.980	0.982	0.978	0.981	0.979	0.982
Flow Entry, veh/h	275	227	306	345	322	363
Cap Entry, veh/h	757	826	1028	1106	1071	1148
V/C Ratio	0.364	0.275	0.298	0.312	0.301	0.316
Control Delay, s/veh	9.3	7.4	6.5	6.3	6.3	6.2
LOS	A	A	A	A	A	A
95th %tile Queue, veh	2	1	1	1	1	1

***Mt. Comfort Road & 2nd Street/PROPOSED
McCord Square Access Drive***

***TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS***

Intersection						
Int Delay, s/veh	0.1					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	FF			FF	FF	
Traffic Vol, veh/h	3	3	1	402	397	0
Future Vol, veh/h	3	3	1	402	397	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	84	84	84	84	84	84
Heavy Vehicles, %	4	4	4	4	4	4
Mvmt Flow	4	4	1	479	473	0
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	954	473	473	0	-	0
Stage 1	473	-	-	-	-	-
Stage 2	481	-	-	-	-	-
Critical Hdwy	6.44	6.24	4.14	-	-	-
Critical Hdwy Stg 1	5.44	-	-	-	-	-
Critical Hdwy Stg 2	5.44	-	-	-	-	-
Follow-up Hdwy	3.536	3.336	2.236	-	-	-
Pot Cap-1 Maneuver	285	587	1079	-	-	-
Stage 1	623	-	-	-	-	-
Stage 2	618	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	285	587	1079	-	-	-
Mov Cap-2 Maneuver	285	-	-	-	-	-
Stage 1	622	-	-	-	-	-
Stage 2	618	-	-	-	-	-
Approach	EB	NB		SB		
HCM Control Delay, s	14.6	0		0		
HCM LOS	B					
Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR	
Capacity (veh/h)	1079	-	384	-	-	
HCM Lane V/C Ratio	0.001	-	0.019	-	-	
HCM Control Delay (s)	8.3	0	14.6	-	-	
HCM Lane LOS	A	A	B	-	-	
HCM 95th %tile Q(veh)	0	-	0.1	-	-	

Intersection						
Int Delay, s/veh	0					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	1	2	1	388	375	2
Future Vol, veh/h	1	2	1	388	375	2
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	1	2	1	422	408	2
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	833	409	410	0	-	0
Stage 1	409	-	-	-	-	-
Stage 2	424	-	-	-	-	-
Critical Hdwy	6.42	6.22	4.12	-	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	2.218	-	-	-
Pot Cap-1 Maneuver	339	642	1149	-	-	-
Stage 1	671	-	-	-	-	-
Stage 2	660	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	339	642	1149	-	-	-
Mov Cap-2 Maneuver	339	-	-	-	-	-
Stage 1	670	-	-	-	-	-
Stage 2	660	-	-	-	-	-
Approach	EB	NB		SB		
HCM Control Delay, s	12.3	0		0		
HCM LOS	B					
Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR	
Capacity (veh/h)	1149	-	495	-	-	
HCM Lane V/C Ratio	0.001	-	0.007	-	-	
HCM Control Delay (s)	8.1	0	12.3	-	-	
HCM Lane LOS	A	A	B	-	-	
HCM 95th %tile Q(veh)	0	-	0	-	-	

Intersection												
Int Delay, s/veh	5.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕		↕	↕			↕	↕	↕	↕	
Traffic Vol, veh/h	3	4	3	51	5	87	1	629	44	68	494	0
Future Vol, veh/h	3	4	3	51	5	87	1	629	44	68	494	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	100	-	-	-	-	100	100	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	84	92	84	92	92	92	84	84	92	92	84	84
Heavy Vehicles, %	4	4	4	4	4	4	4	4	4	4	4	4
Mvmt Flow	4	4	4	55	5	95	1	749	48	74	588	0
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	1561	1535	588	1491	1487	749	588	0	0	797	0	0
Stage 1	736	736	-	751	751	-	-	-	-	-	-	-
Stage 2	825	799	-	740	736	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.14	6.54	6.24	4.14	-	-	4.14	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.536	4.036	3.336	2.236	-	-	2.236	-	-
Pot Cap-1 Maneuver	90	115	505	101	123	409	977	-	-	816	-	-
Stage 1	408	422	-	400	415	-	-	-	-	-	-	-
Stage 2	364	395	-	405	422	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	62	104	505	90	112	409	977	-	-	816	-	-
Mov Cap-2 Maneuver	62	104	-	90	112	-	-	-	-	-	-	-
Stage 1	407	384	-	399	414	-	-	-	-	-	-	-
Stage 2	276	394	-	362	384	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	42.3		46			0			1.1			
HCM LOS	E		E									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1WBLn2	SBL	SBT	SBR					
Capacity (veh/h)	977	-	-	108	90	357	816	-	-			
HCM Lane V/C Ratio	0.001	-	-	0.106	0.616	0.28	0.091	-	-			
HCM Control Delay (s)	8.7	0	-	42.3	94.8	19	9.9	-	-			
HCM Lane LOS	A	A	-	E	F	C	A	-	-			
HCM 95th %tile O(veh)	0	-	-	0.3	2.9	1.1	0.3	-	-			

Intersection												
Int Delay, s/veh	4.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕		↕	↕			↕	↕	↕	↕	
Traffic Vol, veh/h	1	5	2	48	4	77	1	541	54	86	605	2
Future Vol, veh/h	1	5	2	48	4	77	1	541	54	86	605	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	100	-	-	-	-	100	100	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	5	2	52	4	84	1	588	59	93	658	2
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	1509	1494	659	1439	1436	588	660	0	0	647	0	0
Stage 1	845	845	-	590	590	-	-	-	-	-	-	-
Stage 2	664	649	-	849	846	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	99	123	464	111	133	509	928	-	-	939	-	-
Stage 1	357	379	-	494	495	-	-	-	-	-	-	-
Stage 2	450	466	-	356	378	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	74	111	464	98	120	509	928	-	-	939	-	-
Mov Cap-2 Maneuver	74	111	-	98	120	-	-	-	-	-	-	-
Stage 1	356	341	-	493	494	-	-	-	-	-	-	-
Stage 2	372	465	-	314	341	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s	35.4		38.4		0		1.1					
HCM LOS	E		E									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1WBLn2	SBL	SBT	SBR					
Capacity (veh/h)	928	-	-	127 98 439	939	-	-					
HCM Lane V/C Ratio	0.001	-	-	0.068 0.532 0.201	0.1	-	-					
HCM Control Delay (s)	8.9	0	-	35.4 77.5 15.2	9.3	-	-					
HCM Lane LOS	A	A	-	E F C	A	-	-					
HCM 95th %tile O(veh)	0	-	-	0.2 2.4 0.7	0.3	-	-					

HCM 6th Signalized Intersection Summary

3: Mt. Comfort Rd & 2nd St/McCord Square Access

Background + Proposed AM

Mitigated



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕		↕	↕		↕	↕		↕	↕	
Traffic Volume (veh/h)	3	4	3	51	5	87	1	629	44	68	494	0
Future Volume (veh/h)	3	4	3	51	5	87	1	629	44	68	494	0
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1841	1841	1841	1841	1841	1841	1841	1841	1841	1841	1841	1841
Adj Flow Rate, veh/h	4	4	4	55	5	95	1	749	48	74	588	0
Peak Hour Factor	0.84	0.92	0.84	0.92	0.92	0.92	0.84	0.84	0.92	0.92	0.84	0.84
Percent Heavy Veh, %	4	4	4	4	4	4	4	4	4	4	4	4
Cap, veh/h	180	165	121	473	18	341	439	953	61	297	1025	0
Arrive On Green	0.23	0.23	0.23	0.23	0.23	0.23	0.56	0.56	0.56	0.56	0.56	0.00
Sat Flow, veh/h	339	724	532	1385	79	1493	815	1711	110	671	1841	0
Grp Volume(v), veh/h	12	0	0	55	0	100	1	0	797	74	588	0
Grp Sat Flow(s),veh/h/ln	1595	0	0	1385	0	1572	815	0	1821	671	1841	0
Q Serve(g_s), s	0.0	0.0	0.0	1.2	0.0	2.4	0.0	0.0	16.0	4.5	9.7	0.0
Cycle Q Clear(g_c), s	0.2	0.0	0.0	1.4	0.0	2.4	9.7	0.0	16.0	20.6	9.7	0.0
Prop In Lane	0.33		0.33	1.00		0.95	1.00		0.06	1.00		0.00
Lane Grp Cap(c), veh/h	467	0	0	473	0	359	439	0	1014	297	1025	0
V/C Ratio(X)	0.03	0.00	0.00	0.12	0.00	0.28	0.00	0.00	0.79	0.25	0.57	0.00
Avail Cap(c_a), veh/h	512	0	0	514	0	405	563	0	1292	399	1306	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	0.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	14.0	0.0	0.0	14.4	0.0	14.8	9.9	0.0	8.1	16.2	6.7	0.0
Incr Delay (d2), s/veh	0.0	0.0	0.0	0.1	0.0	0.4	0.0	0.0	2.5	0.4	0.5	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.1	0.0	0.0	0.4	0.0	0.8	0.0	0.0	4.8	0.6	2.6	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	14.0	0.0	0.0	14.5	0.0	15.2	9.9	0.0	10.7	16.7	7.2	0.0
LnGrp LOS	B	A	A	B	A	B	A	A	B	B	A	A
Approach Vol, veh/h	12		155			798			662			
Approach Delay, s/veh	14.0		15.0			10.7			8.3			
Approach LOS	B		B			B			A			
Timer - Assigned Phs	2		4		6		8					
Phs Duration (G+Y+Rc), s	30.9		15.6		30.9		15.6					
Change Period (Y+Rc), s	5.0		5.0		5.0		5.0					
Max Green Setting (Gmax), s	33.0		12.0		33.0		12.0					
Max Q Clear Time (g_c+I1), s	18.0		2.2		22.6		4.4					
Green Ext Time (p_c), s	5.2		0.0		3.3		0.4					
Intersection Summary												
HCM 6th Ctrl Delay			10.1									
HCM 6th LOS			B									

HCM 6th Signalized Intersection Summary

3: Mt. Comfort Rd & 2nd St/McCord Square Access

Background + Proposed PM
Mitigated



Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔		↔	↔		↔	↔		↔	↔	
Traffic Volume (veh/h)	1	5	2	48	4	77	1	541	54	86	605	2
Future Volume (veh/h)	1	5	2	48	4	77	1	541	54	86	605	2
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	1	5	2	52	4	84	1	588	59	93	658	2
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2	2	2	2	2	2	2
Cap, veh/h	116	302	106	518	17	366	369	857	86	372	955	3
Arrive On Green	0.24	0.24	0.24	0.24	0.24	0.24	0.51	0.51	0.51	0.51	0.51	0.51
Sat Flow, veh/h	66	1255	441	1409	73	1524	774	1672	168	784	1864	6
Grp Volume(v), veh/h	8	0	0	52	0	88	1	0	647	93	0	660
Grp Sat Flow(s),veh/h/ln	1763	0	0	1409	0	1596	774	0	1840	784	0	1869
Q Serve(g_s), s	0.0	0.0	0.0	1.0	0.0	1.8	0.0	0.0	10.7	4.1	0.0	10.8
Cycle Q Clear(g_c), s	0.1	0.0	0.0	1.1	0.0	1.8	10.8	0.0	10.7	14.8	0.0	10.8
Prop In Lane	0.12		0.25	1.00		0.95	1.00		0.09	1.00		0.00
Lane Grp Cap(c), veh/h	524	0	0	518	0	384	369	0	943	372	0	958
V/C Ratio(X)	0.02	0.00	0.00	0.10	0.00	0.23	0.00	0.00	0.69	0.25	0.00	0.69
Avail Cap(c_a), veh/h	620	0	0	597	0	473	508	0	1274	513	0	1294
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	0.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00
Uniform Delay (d), s/veh	11.7	0.0	0.0	12.1	0.0	12.4	11.5	0.0	7.4	13.0	0.0	7.4
Incr Delay (d2), s/veh	0.0	0.0	0.0	0.1	0.0	0.3	0.0	0.0	0.9	0.3	0.0	1.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.0	0.0	0.0	0.3	0.0	0.6	0.0	0.0	2.8	0.6	0.0	2.9
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	11.7	0.0	0.0	12.2	0.0	12.7	11.5	0.0	8.4	13.3	0.0	8.4
LnGrp LOS	B	A	A	B	A	B	B	A	A	B	A	A
Approach Vol, veh/h		8			140			648			753	
Approach Delay, s/veh		11.7			12.5			8.4			9.0	
Approach LOS		B			B			A			A	
Timer - Assigned Phs		2		4		6		8				
Phs Duration (G+Y+Rc), s		25.7		14.7		25.7		14.7				
Change Period (Y+Rc), s		5.0		5.0		5.0		5.0				
Max Green Setting (Gmax), s		28.0		12.0		28.0		12.0				
Max Q Clear Time (g_c+I1), s		12.8		2.1		16.8		3.8				
Green Ext Time (p_c), s		4.0		0.0		3.9		0.3				
Intersection Summary												
HCM 6th Ctrl Delay				9.1								
HCM 6th LOS				A								

SR 234 & BROADWAY

TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS

HCM 6th Signalized Intersection Summary

4: Broadway & SR 234

Existing AM
10/22/2021

						
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations						
Traffic Volume (veh/h)	236	1	313	247	0	503
Future Volume (veh/h)	236	1	313	247	0	503
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00	1.00		1.00	1.00	
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No		No			No
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826
Adj Flow Rate, veh/h	251	1	333	0	0	535
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94
Percent Heavy Veh, %	5	5	5	5	5	5
Cap, veh/h	545	2	722		0	722
Arrive On Green	0.32	0.32	0.40	0.00	0.00	0.40
Sat Flow, veh/h	1725	7	1826	1547	0	1826
Grp Volume(v), veh/h	253	0	333	0	0	535
Grp Sat Flow(s),veh/h/ln	1738	0	1826	1547	0	1826
Q Serve(g_s), s	4.0	0.0	4.7	0.0	0.0	8.7
Cycle Q Clear(g_c), s	4.0	0.0	4.7	0.0	0.0	8.7
Prop In Lane	0.99	0.00		1.00	0.00	
Lane Grp Cap(c), veh/h	549	0	722		0	722
V/C Ratio(X)	0.46	0.00	0.46		0.00	0.74
Avail Cap(c_a), veh/h	753	0	1317		0	1317
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	0.00	0.00	1.00
Uniform Delay (d), s/veh	9.5	0.0	7.7	0.0	0.0	9.0
Incr Delay (d2), s/veh	0.6	0.0	0.5	0.0	0.0	1.5
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.2	0.0	1.3	0.0	0.0	2.5
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	10.1	0.0	8.2	0.0	0.0	10.5
LnGrp LOS	B	A	A		A	B
Approach Vol, veh/h	253		333	A		535
Approach Delay, s/veh	10.1		8.2			10.5
Approach LOS	B		A			B
Timer - Assigned Phs		2			6	8
Phs Duration (G+Y+Rc), s		18.7			18.7	15.9
Change Period (Y+Rc), s		5.0			5.0	5.0
Max Green Setting (Gmax), s		25.0			25.0	15.0
Max Q Clear Time (g_c+I1), s		6.7			10.7	6.0
Green Ext Time (p_c), s		1.9			3.0	0.5
Intersection Summary						
HCM 6th Ctrl Delay			9.7			
HCM 6th LOS			A			
Notes						
User approved volume balancing among the lanes for turning movement.						
Unsignalized Delay for [NER] is excluded from calculations of the approach delay and intersection delay.						

HCM 6th Signalized Intersection Summary

4: Broadway & SR 234

Existing PM
10/22/2021

						
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations						
Traffic Volume (veh/h)	158	1	529	201	1	367
Future Volume (veh/h)	158	1	529	201	1	367
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00	1.00		1.00	1.00	
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No		No			No
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	172	1	575	0	1	399
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2
Cap, veh/h	501	3	788		107	787
Arrive On Green	0.28	0.28	0.42	0.00	0.42	0.42
Sat Flow, veh/h	1760	10	1870	1585	1	1868
Grp Volume(v), veh/h	174	0	575	0	400	0
Grp Sat Flow(s),veh/h/ln	1781	0	1870	1585	1869	0
Q Serve(g_s), s	2.6	0.0	8.7	0.0	0.0	0.0
Cycle Q Clear(g_c), s	2.6	0.0	8.7	0.0	5.4	0.0
Prop In Lane	0.99	0.01		1.00	0.00	
Lane Grp Cap(c), veh/h	507	0	788		893	0
V/C Ratio(X)	0.34	0.00	0.73		0.45	0.00
Avail Cap(c_a), veh/h	628	0	1540		1644	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	0.00	1.00	0.00
Uniform Delay (d), s/veh	9.6	0.0	8.2	0.0	7.2	0.0
Incr Delay (d2), s/veh	0.4	0.0	1.3	0.0	0.4	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.8	0.0	2.4	0.0	1.4	0.0
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	10.0	0.0	9.5	0.0	7.6	0.0
LnGrp LOS	B	A	A		A	A
Approach Vol, veh/h	174		575	A		400
Approach Delay, s/veh	10.0		9.5			7.6
Approach LOS	B		A			A
Timer - Assigned Phs		2			6	8
Phs Duration (G+Y+Rc), s		19.3			19.3	14.7
Change Period (Y+Rc), s		5.0			5.0	5.0
Max Green Setting (Gmax), s		28.0			28.0	12.0
Max Q Clear Time (g_c+l1), s		10.7			7.4	4.6
Green Ext Time (p_c), s		3.6			2.4	0.3
Intersection Summary						
HCM 6th Ctrl Delay			8.9			
HCM 6th LOS			A			
Notes						
User approved volume balancing among the lanes for turning movement.						
Unsignalized Delay for [NER] is excluded from calculations of the approach delay and intersection delay.						

Intersection						
Int Delay, s/veh	0.1					
Movement	EBL	EBR	NEL	NET	SWT	SWR
Lane Configurations	↔			↕↕	↕	
Traffic Vol, veh/h	5	3	0	555	591	148
Future Vol, veh/h	5	3	0	555	591	148
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	94	94	94	94	94	94
Heavy Vehicles, %	5	5	5	5	5	5
Mvmt Flow	5	3	0	590	629	157
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	1003	708	786	0	-	0
Stage 1	708	-	-	-	-	-
Stage 2	295	-	-	-	-	-
Critical Hdwy	6.675	6.275	4.175	-	-	-
Critical Hdwy Stg 1	5.475	-	-	-	-	-
Critical Hdwy Stg 2	5.875	-	-	-	-	-
Follow-up Hdwy	3.5475	3.3475	2.2475	-	-	-
Pot Cap-1 Maneuver	249	427	815	-	-	-
Stage 1	480	-	-	-	-	-
Stage 2	723	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	249	427	815	-	-	-
Mov Cap-2 Maneuver	249	-	-	-	-	-
Stage 1	480	-	-	-	-	-
Stage 2	723	-	-	-	-	-
Approach	EB	NE		SW		
HCM Control Delay, s	17.6	0		0		
HCM LOS	C					
Minor Lane/Major Mvmt	NEL	NET	EBLn1	SWT	SWR	
Capacity (veh/h)	815	-	295	-	-	
HCM Lane V/C Ratio	-	-	0.029	-	-	
HCM Control Delay (s)	0	-	17.6	-	-	
HCM Lane LOS	A	-	C	-	-	
HCM 95th %tile Q(veh)	0	-	0.1	-	-	

Intersection

Int Delay, s/veh 0

Movement EBL EBR NEL NET SWT SWR

Lane Configurations      

Traffic Vol, veh/h 1 0 2 729 435 120

Future Vol, veh/h 1 0 2 729 435 120

Conflicting Peds, #/hr 0 0 0 0 0 0

Sign Control Stop Stop Free Free Free Free

RT Channelized - None - None - None

Storage Length 0 - - - - -

Veh in Median Storage, # 0 - - 0 0 -

Grade, % 0 - - 0 0 -

Peak Hour Factor 96 96 96 96 96 96

Heavy Vehicles, % 2 2 2 2 2 2

Mvmt Flow 1 0 2 759 453 125

Major/Minor Minor2 Major1 Major2

Conflicting Flow All 900 516 578 0 - 0

Stage 1 516 - - - - -

Stage 2 384 - - - - -

Critical Hdwy 6.63 6.23 4.13 - - -

Critical Hdwy Stg 1 5.43 - - - - -

Critical Hdwy Stg 2 5.83 - - - - -

Follow-up Hdwy 3.519 3.319 2.219 - - -

Pot Cap-1 Maneuver 293 558 994 - - -

Stage 1 598 - - - - -

Stage 2 659 - - - - -

Platoon blocked, % - - - - -

Mov Cap-1 Maneuver 292 558 994 - - -

Mov Cap-2 Maneuver 292 - - - - -

Stage 1 596 - - - - -

Stage 2 659 - - - - -

Approach EB NE SW

HCM Control Delay, s 17.4 0 0

HCM LOS C

Minor Lane/Major Mvmt NEL NET EBLn1 SWT SWR

Capacity (veh/h) 994 - 292 - -

HCM Lane V/C Ratio 0.002 - 0.004 - -

HCM Control Delay (s) 8.6 0 17.4 - -

HCM Lane LOS A A C - -

HCM 95th %tile Q(veh) 0 - 0 - -

HCM 6th Signalized Intersection Summary

4: Broadway & SR 234

Background + Proposed AM

10/25/2021

						
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations						
Traffic Volume (veh/h)	281	3	425	287	1	604
Future Volume (veh/h)	281	3	425	287	1	604
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00	1.00		1.00	1.00	
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No		No			No
Adj Sat Flow, veh/h/ln	1826	1826	1826	1826	1826	1826
Adj Flow Rate, veh/h	299	3	452	0	1	643
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94
Percent Heavy Veh, %	5	5	5	5	5	5
Cap, veh/h	508	5	816		93	816
Arrive On Green	0.30	0.30	0.45	0.00	0.45	0.45
Sat Flow, veh/h	1714	17	1826	1547	0	1825
Grp Volume(v), veh/h	303	0	452	0	644	0
Grp Sat Flow(s),veh/h/ln	1737	0	1826	1547	1825	0
Q Serve(g_s), s	5.8	0.0	7.1	0.0	0.0	0.0
Cycle Q Clear(g_c), s	5.8	0.0	7.1	0.0	11.7	0.0
Prop In Lane	0.99	0.01		1.00	0.00	
Lane Grp Cap(c), veh/h	515	0	816		909	0
V/C Ratio(X)	0.59	0.00	0.55		0.71	0.00
Avail Cap(c_a), veh/h	579	0	1265		1356	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	0.00	1.00	0.00
Uniform Delay (d), s/veh	11.7	0.0	7.9	0.0	9.2	0.0
Incr Delay (d2), s/veh	1.3	0.0	0.6	0.0	1.0	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.9	0.0	2.0	0.0	3.4	0.0
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	12.9	0.0	8.5	0.0	10.2	0.0
LnGrp LOS	B	A	A		B	A
Approach Vol, veh/h	303		452	A		644
Approach Delay, s/veh	12.9		8.5			10.2
Approach LOS	B		A			B
Timer - Assigned Phs		2			6	8
Phs Duration (G+Y+Rc), s		22.4			22.4	16.5
Change Period (Y+Rc), s		5.0			5.0	5.0
Max Green Setting (Gmax), s		27.0			27.0	13.0
Max Q Clear Time (g_c+I1), s		9.1			13.7	7.8
Green Ext Time (p_c), s		2.7			3.7	0.4
Intersection Summary						
HCM 6th Ctrl Delay			10.3			
HCM 6th LOS			B			
Notes						
User approved volume balancing among the lanes for turning movement.						
Unsignalized Delay for [NER] is excluded from calculations of the approach delay and intersection delay.						

HCM 6th Signalized Intersection Summary

4: Broadway & SR 234

Background + Proposed PM
10/25/2021

						
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations						
Traffic Volume (veh/h)	196	2	656	243	5	498
Future Volume (veh/h)	196	2	656	243	5	498
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00	1.00		1.00	1.00	
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No		No			No
Adj Sat Flow, veh/h/ln	1870	1870	1870	1870	1870	1870
Adj Flow Rate, veh/h	213	2	713	0	5	541
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92
Percent Heavy Veh, %	2	2	2	2	2	2
Cap, veh/h	479	4	892		93	887
Arrive On Green	0.27	0.27	0.48	0.00	0.48	0.48
Sat Flow, veh/h	1755	16	1870	1585	4	1860
Grp Volume(v), veh/h	216	0	713	0	546	0
Grp Sat Flow(s),veh/h/ln	1780	0	1870	1585	1864	0
Q Serve(g_s), s	4.0	0.0	12.9	0.0	0.0	0.0
Cycle Q Clear(g_c), s	4.0	0.0	12.9	0.0	8.6	0.0
Prop In Lane	0.99	0.01		1.00	0.01	
Lane Grp Cap(c), veh/h	486	0	892		980	0
V/C Ratio(X)	0.44	0.00	0.80		0.56	0.00
Avail Cap(c_a), veh/h	535	0	1311		1393	0
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	0.00	1.00	0.00	1.00	0.00
Uniform Delay (d), s/veh	12.0	0.0	8.8	0.0	7.7	0.0
Incr Delay (d2), s/veh	0.6	0.0	2.2	0.0	0.5	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	1.4	0.0	3.9	0.0	2.4	0.0
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	12.7	0.0	11.1	0.0	8.2	0.0
LnGrp LOS	B	A	B		A	A
Approach Vol, veh/h	216		713	A		546
Approach Delay, s/veh	12.7		11.1			8.2
Approach LOS	B		B			A
Timer - Assigned Phs		2			6	8
Phs Duration (G+Y+Rc), s		24.0			24.0	15.9
Change Period (Y+Rc), s		5.0			5.0	5.0
Max Green Setting (Gmax), s		28.0			28.0	12.0
Max Q Clear Time (g_c+I1), s		14.9			10.6	6.0
Green Ext Time (p_c), s		4.2			3.4	0.3
Intersection Summary						
HCM 6th Ctrl Delay			10.3			
HCM 6th LOS			B			
Notes						
User approved volume balancing among the lanes for turning movement.						
Unsignalized Delay for [NER] is excluded from calculations of the approach delay and intersection delay.						

Intersection						
Int Delay, s/veh	0.1					
Movement	EBL	EBR	NEL	NET	SWT	SWR
Lane Configurations						
Traffic Vol, veh/h	5	3	0	707	722	163
Future Vol, veh/h	5	3	0	707	722	163
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	94	94	94	94	94	94
Heavy Vehicles, %	5	5	5	5	5	5
Mvmt Flow	5	3	0	752	768	173
Major/Minor	Minor2	Major1	Major2			
Conflicting Flow All	1231	855	941	0	-	0
Stage 1	855	-	-	-	-	-
Stage 2	376	-	-	-	-	-
Critical Hdwy	6.675	6.275	4.175	-	-	-
Critical Hdwy Stg 1	5.475	-	-	-	-	-
Critical Hdwy Stg 2	5.875	-	-	-	-	-
Follow-up Hdwy	3.5475	3.3475	2.2475	-	-	-
Pot Cap-1 Maneuver	179	351	711	-	-	-
Stage 1	409	-	-	-	-	-
Stage 2	657	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	179	351	711	-	-	-
Mov Cap-2 Maneuver	179	-	-	-	-	-
Stage 1	409	-	-	-	-	-
Stage 2	657	-	-	-	-	-
Approach	EB	NE	SW			
HCM Control Delay, s	22.1	0	0			
HCM LOS	C					
Minor Lane/Major Mvmt	NEL	NET	EBLn1	SWT	SWR	
Capacity (veh/h)	711	-	219	-	-	
HCM Lane V/C Ratio	-	-	0.039	-	-	
HCM Control Delay (s)	0	-	22.1	-	-	
HCM Lane LOS	A	-	C	-	-	
HCM 95th %tile Q(veh)	0	-	0.1	-	-	

Intersection

Int Delay, s/veh 0

Movement EBL EBR NEL NET SWT SWR

Lane Configurations      

Traffic Vol, veh/h 1 0 2 898 595 99

Future Vol, veh/h 1 0 2 898 595 99

Conflicting Peds, #/hr 0 0 0 0 0 0

Sign Control Stop Stop Free Free Free Free

RT Channelized - None - None - None

Storage Length 0 - - - - -

Veh in Median Storage, # 0 - - 0 0 -

Grade, % 0 - - 0 0 -

Peak Hour Factor 96 96 96 96 96 96

Heavy Vehicles, % 2 2 2 2 2 2

Mvmt Flow 1 0 2 935 620 103

Major/Minor Minor2 Major1 Major2

Conflicting Flow All 1144 672 723 0 - 0

Stage 1 672 - - - - -

Stage 2 472 - - - - -

Critical Hdwy 6.63 6.23 4.13 - - -

Critical Hdwy Stg 1 5.43 - - - - -

Critical Hdwy Stg 2 5.83 - - - - -

Follow-up Hdwy 3.519 3.319 2.219 - - -

Pot Cap-1 Maneuver 207 455 877 - - -

Stage 1 506 - - - - -

Stage 2 595 - - - - -

Platoon blocked, % - - - - -

Mov Cap-1 Maneuver 206 455 877 - - -

Mov Cap-2 Maneuver 206 - - - - -

Stage 1 503 - - - - -

Stage 2 595 - - - - -

Approach EB NE SW

HCM Control Delay, s 22.6 0 0

HCM LOS C

Minor Lane/Major Mvmt NEL NET EBLn1 SWT SWR

Capacity (veh/h) 877 - 206 - -

HCM Lane V/C Ratio 0.002 - 0.005 - -

HCM Control Delay (s) 9.1 0 22.6 - -

HCM Lane LOS A A C - -

HCM 95th %tile Q(veh) 0 - 0 - -

SR 234 & CR 500 W

TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	5.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	1	247	5	19	230	26	11	22	72	55	58	2
Future Vol, veh/h	1	247	5	19	230	26	11	22	72	55	58	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	81	81	81	81	81	81	81	81	81	81	81	81
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	1	305	6	23	284	32	14	27	89	68	72	2
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	316	0	0	311	0	0	693	672	308	714	659	300
Stage 1	-	-	-	-	-	-	310	310	-	346	346	-
Stage 2	-	-	-	-	-	-	383	362	-	368	313	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1244	-	-	1249	-	-	358	377	732	346	384	740
Stage 1	-	-	-	-	-	-	700	659	-	670	635	-
Stage 2	-	-	-	-	-	-	640	625	-	652	657	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1244	-	-	1249	-	-	299	368	732	282	375	740
Mov Cap-2 Maneuver	-	-	-	-	-	-	299	368	-	282	375	-
Stage 1	-	-	-	-	-	-	699	658	-	669	621	-
Stage 2	-	-	-	-	-	-	552	611	-	549	656	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0			0.5			13.8			24.3		
HCM LOS							B			C		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	539	1244	-	-	1249	-	-	326				
HCM Lane V/C Ratio	0.241	0.001	-	-	0.019	-	-	0.436				
HCM Control Delay (s)	13.8	7.9	0	-	7.9	0	-	24.3				
HCM Lane LOS	B	A	A	-	A	A	-	C				
HCM 95th %tile Q(veh)	0.9	0	-	-	0.1	-	-	2.1				

Intersection												
Int Delay, s/veh	4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	5	173	7	14	164	22	3	72	14	24	32	1
Future Vol, veh/h	5	173	7	14	164	22	3	72	14	24	32	1
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	89	89	89	89	89	89	89	89	89	89	89	89
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	6	194	8	16	184	25	3	81	16	27	36	1
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	209	0	0	202	0	0	457	451	198	488	443	197
Stage 1	-	-	-	-	-	-	210	210	-	229	229	-
Stage 2	-	-	-	-	-	-	247	241	-	259	214	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1362	-	-	1370	-	-	514	504	843	490	509	844
Stage 1	-	-	-	-	-	-	792	728	-	774	715	-
Stage 2	-	-	-	-	-	-	757	706	-	746	725	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1362	-	-	1370	-	-	479	495	843	415	500	844
Mov Cap-2 Maneuver	-	-	-	-	-	-	479	495	-	415	500	-
Stage 1	-	-	-	-	-	-	788	724	-	770	706	-
Stage 2	-	-	-	-	-	-	708	697	-	647	721	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0.2			0.5			13.4			14		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	529	1362	-	-	1370	-	-	463				
HCM Lane V/C Ratio	0.189	0.004	-	-	0.011	-	-	0.138				
HCM Control Delay (s)	13.4	7.7	0	-	7.7	0	-	14				
HCM Lane LOS	B	A	A	-	A	A	-	B				
HCM 95th %tile Q(veh)	0.7	0	-	-	0	-	-	0.5				

Intersection												
Int Delay, s/veh	22.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	10	305	7	39	285	29	15	64	132	61	77	12
Future Vol, veh/h	10	305	7	39	285	29	15	64	132	61	77	12
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	81	81	81	81	81	81	81	81	81	81	81	81
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	12	377	9	48	352	36	19	79	163	75	95	15
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	388	0	0	386	0	0	927	890	382	993	876	370
Stage 1	-	-	-	-	-	-	406	406	-	466	466	-
Stage 2	-	-	-	-	-	-	521	484	-	527	410	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1170	-	-	1172	-	-	249	282	665	224	287	676
Stage 1	-	-	-	-	-	-	622	598	-	577	562	-
Stage 2	-	-	-	-	-	-	539	552	-	535	595	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1170	-	-	1172	-	-	169	264	665	124	269	676
Mov Cap-2 Maneuver	-	-	-	-	-	-	169	264	-	124	269	-
Stage 1	-	-	-	-	-	-	614	590	-	569	533	-
Stage 2	-	-	-	-	-	-	411	523	-	345	587	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0.3			0.9			29.6			113		
HCM LOS							D			F		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	398	1170	-	-	1172	-	-	188				
HCM Lane V/C Ratio	0.655	0.011	-	-	0.041	-	-	0.985				
HCM Control Delay (s)	29.6	8.1	0	-	8.2	0	-	113				
HCM Lane LOS	D	A	A	-	A	A	-	F				
HCM 95th %tile Q(veh)	4.5	0	-	-	0.1	-	-	8.2				

Intersection												
Int Delay, s/veh	8.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	13	226	11	73	224	24	6	106	50	26	76	13
Future Vol, veh/h	13	226	11	73	224	24	6	106	50	26	76	13
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	89	89	89	89	89	89	89	89	89	89	89	89
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	15	254	12	82	252	27	7	119	56	29	85	15
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	279	0	0	266	0	0	770	733	260	808	726	266
Stage 1	-	-	-	-	-	-	290	290	-	430	430	-
Stage 2	-	-	-	-	-	-	480	443	-	378	296	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1284	-	-	1298	-	-	318	348	779	299	351	773
Stage 1	-	-	-	-	-	-	718	672	-	603	583	-
Stage 2	-	-	-	-	-	-	567	576	-	644	668	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1284	-	-	1298	-	-	232	317	779	184	320	773
Mov Cap-2 Maneuver	-	-	-	-	-	-	232	317	-	184	320	-
Stage 1	-	-	-	-	-	-	708	663	-	595	539	-
Stage 2	-	-	-	-	-	-	433	533	-	483	659	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0.4			1.8			22.7			26.9		
HCM LOS							C			D		
Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1				
Capacity (veh/h)	382	1284	-	-	1298	-	-	291				
HCM Lane V/C Ratio	0.476	0.011	-	-	0.063	-	-	0.444				
HCM Control Delay (s)	22.7	7.8	0	-	8	0	-	26.9				
HCM Lane LOS	C	A	A	-	A	A	-	D				
HCM 95th %tile Q(veh)	2.5	0	-	-	0.2	-	-	2.2				

Intersection				
Intersection Delay, s/veh 6.9				
Intersection LOS A				
Approach	EB	WB	NB	SB
Entry Lanes	1	1	1	1
Conflicting Circle Lanes	1	1	1	1
Adj Approach Flow, veh/h	398	436	261	185
Demand Flow Rate, veh/h	406	445	266	188
Vehicles Circulating, veh/h	222	112	473	427
Vehicles Exiting, veh/h	393	627	155	130
Ped Vol Crossing Leg, #/h	0	0	0	0
Ped Cap Adj	1.000	1.000	1.000	1.000
Approach Delay, s/veh	7.1	6.5	7.8	6.2
Approach LOS	A	A	A	A
Lane	Left	Left	Left	Left
Designated Moves	LTR	LTR	LTR	LTR
Assumed Moves	LTR	LTR	LTR	LTR
RT Channelized				
Lane Util	1.000	1.000	1.000	1.000
Follow-Up Headway, s	2.609	2.609	2.609	2.609
Critical Headway, s	4.976	4.976	4.976	4.976
Entry Flow, veh/h	406	445	266	188
Cap Entry Lane, veh/h	1100	1231	852	893
Entry HV Adj Factor	0.981	0.980	0.983	0.985
Flow Entry, veh/h	398	436	261	185
Cap Entry, veh/h	1080	1206	837	879
V/C Ratio	0.369	0.362	0.312	0.211
Control Delay, s/veh	7.1	6.5	7.8	6.2
LOS	A	A	A	A
95th %tile Queue, veh	2	2	1	1

Intersection

Intersection Delay, s/veh 5.6

Intersection LOS A

Approach	EB	WB	NB	SB
Entry Lanes	1	1	1	1
Conflicting Circle Lanes	1	1	1	1
Adj Approach Flow, veh/h	281	361	182	129
Demand Flow Rate, veh/h	286	369	185	132
Vehicles Circulating, veh/h	201	143	304	348
Vehicles Exiting, veh/h	279	346	183	164
Ped Vol Crossing Leg, #/h	0	0	0	0
Ped Cap Adj	1.000	1.000	1.000	1.000
Approach Delay, s/veh	5.6	6.0	5.3	5.1
Approach LOS	A	A	A	A

Lane	Left	Left	Left	Left
Designated Moves	LTR	LTR	LTR	LTR
Assumed Moves	LTR	LTR	LTR	LTR
RT Channelized				
Lane Util	1.000	1.000	1.000	1.000
Follow-Up Headway, s	2.609	2.609	2.609	2.609
Critical Headway, s	4.976	4.976	4.976	4.976
Entry Flow, veh/h	286	369	185	132
Cap Entry Lane, veh/h	1124	1193	1012	968
Entry HV Adj Factor	0.982	0.978	0.982	0.980
Flow Entry, veh/h	281	361	182	129
Cap Entry, veh/h	1104	1167	994	948
V/C Ratio	0.254	0.309	0.183	0.136
Control Delay, s/veh	5.6	6.0	5.3	5.1
LOS	A	A	A	A
95th %tile Queue, veh	1	1	1	0

CR 750 N & CR 500 W

TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS

Intersection						
Int Delay, s/veh	2.1					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	29	5	14	79	68	10
Future Vol, veh/h	29	5	14	79	68	10
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	3	3	3	3	3	3
Mvmt Flow	34	6	16	93	80	12
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	211	86	92	0	-	0
Stage 1	86	-	-	-	-	-
Stage 2	125	-	-	-	-	-
Critical Hdwy	6.43	6.23	4.13	-	-	-
Critical Hdwy Stg 1	5.43	-	-	-	-	-
Critical Hdwy Stg 2	5.43	-	-	-	-	-
Follow-up Hdwy	3.527	3.327	2.227	-	-	-
Pot Cap-1 Maneuver	775	970	1496	-	-	-
Stage 1	935	-	-	-	-	-
Stage 2	898	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	766	970	1496	-	-	-
Mov Cap-2 Maneuver	766	-	-	-	-	-
Stage 1	925	-	-	-	-	-
Stage 2	898	-	-	-	-	-
Approach	EB	NB		SB		
HCM Control Delay, s	9.8	1.1		0		
HCM LOS	A					
Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR	
Capacity (veh/h)	1496	-	790	-	-	
HCM Lane V/C Ratio	0.011	-	0.051	-	-	
HCM Control Delay (s)	7.4	0	9.8	-	-	
HCM Lane LOS	A	A	A	-	-	
HCM 95th %tile Q(veh)	0	-	0.2	-	-	

Intersection

Int Delay, s/veh 1.5

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations	W			W	W	
Traffic Vol, veh/h	9	15	2	81	41	5
Future Vol, veh/h	9	15	2	81	41	5
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	11	18	2	95	48	6

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	150	51	54
Stage 1	51	-	-
Stage 2	99	-	-
Critical Hdwy	6.4	6.2	4.1
Critical Hdwy Stg 1	5.4	-	-
Critical Hdwy Stg 2	5.4	-	-
Follow-up Hdwy	3.5	3.3	2.2
Pot Cap-1 Maneuver	847	1023	1564
Stage 1	977	-	-
Stage 2	930	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	846	1023	1564
Mov Cap-2 Maneuver	846	-	-
Stage 1	976	-	-
Stage 2	930	-	-

Approach	EB	NB	SB
HCM Control Delay, s	8.9	0.2	0
HCM LOS	A		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	1564	-	949	-	-
HCM Lane V/C Ratio	0.002	-	0.03	-	-
HCM Control Delay (s)	7.3	0	8.9	-	-
HCM Lane LOS	A	A	A	-	-
HCM 95th %tile Q(veh)	0	-	0.1	-	-

Intersection

Int Delay, s/veh 3.9

Movement EBL EBR NBL NBT SBT SBR

Lane Configurations	W			W	W	
Traffic Vol, veh/h	77	27	36	112	87	34
Future Vol, veh/h	77	27	36	112	87	34
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	3	3	3	3	3	3
Mvmt Flow	91	32	42	132	102	40

Major/Minor Minor2 Major1 Major2

Conflicting Flow All	338	122	142	0	-	0
Stage 1	122	-	-	-	-	-
Stage 2	216	-	-	-	-	-
Critical Hdwy	6.43	6.23	4.13	-	-	-
Critical Hdwy Stg 1	5.43	-	-	-	-	-
Critical Hdwy Stg 2	5.43	-	-	-	-	-
Follow-up Hdwy	3.527	3.327	2.227	-	-	-
Pot Cap-1 Maneuver	656	926	1435	-	-	-
Stage 1	901	-	-	-	-	-
Stage 2	818	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	635	926	1435	-	-	-
Mov Cap-2 Maneuver	635	-	-	-	-	-
Stage 1	872	-	-	-	-	-
Stage 2	818	-	-	-	-	-

Approach EB NB SB

HCM Control Delay, s	11.3	1.8	0
HCM LOS	B		

Minor Lane/Major Mvmt NBL NBT EBLn1 SBT SBR

Capacity (veh/h)	1435	-	691	-	-
HCM Lane V/C Ratio	0.03	-	0.177	-	-
HCM Control Delay (s)	7.6	0	11.3	-	-
HCM Lane LOS	A	A	B	-	-
HCM 95th %tile Q(veh)	0.1	-	0.6	-	-

Intersection

Int Delay, s/veh 3.2

Movement EBL EBR NBL NBT SBT SBR

Lane Configurations 

Traffic Vol, veh/h 49 37 34 111 72 60

Future Vol, veh/h 49 37 34 111 72 60

Conflicting Peds, #/hr 0 0 0 0 0 0

Sign Control Stop Stop Free Free Free Free

RT Channelized - None - None - None

Storage Length 0 - - - - -

Veh in Median Storage, # 0 - - 0 0 -

Grade, % 0 - - 0 0 -

Peak Hour Factor 85 85 85 85 85 85

Heavy Vehicles, % 0 0 0 0 0 0

Mvmt Flow 58 44 40 131 85 71

Major/Minor Minor2 Major1 Major2

Conflicting Flow All 332 121 156 0 - 0

Stage 1 121 - - - - -

Stage 2 211 - - - - -

Critical Hdwy 6.4 6.2 4.1 - - -

Critical Hdwy Stg 1 5.4 - - - - -

Critical Hdwy Stg 2 5.4 - - - - -

Follow-up Hdwy 3.5 3.3 2.2 - - -

Pot Cap-1 Maneuver 667 936 1436 - - -

Stage 1 909 - - - - -

Stage 2 829 - - - - -

Platoon blocked, % - - - - -

Mov Cap-1 Maneuver 647 936 1436 - - -

Mov Cap-2 Maneuver 647 - - - - -

Stage 1 882 - - - - -

Stage 2 829 - - - - -

Approach EB NB SB

HCM Control Delay, s 10.6 1.8 0

HCM LOS B

Minor Lane/Major Mvmt NBL NBT EBLn1 SBT SBR

Capacity (veh/h) 1436 - 746 - -

HCM Lane V/C Ratio 0.028 - 0.136 - -

HCM Control Delay (s) 7.6 0 10.6 - -

HCM Lane LOS A A B - -

HCM 95th %tile Q(veh) 0.1 - 0.5 - -

CR 700 N & CR 500 W

TRAFFIC VOLUME COUNTS
CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	1.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	3	8	0	1	13	9	2	81	2	3	69	9
Future Vol, veh/h	3	8	0	1	13	9	2	81	2	3	69	9
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	88	88	88	88	88	88	88	88	88	88	88	88
Heavy Vehicles, %	4	4	4	4	4	4	4	4	4	4	4	4
Mvmt Flow	3	9	0	1	15	10	2	92	2	3	78	10
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	199	187	83	191	191	93	88	0	0	94	0	0
Stage 1	89	89	-	97	97	-	-	-	-	-	-	-
Stage 2	110	98	-	94	94	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.14	6.54	6.24	4.14	-	-	4.14	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.536	4.036	3.336	2.236	-	-	2.236	-	-
Pot Cap-1 Maneuver	755	704	971	764	700	959	1495	-	-	1488	-	-
Stage 1	914	817	-	905	811	-	-	-	-	-	-	-
Stage 2	890	810	-	908	813	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	733	702	971	755	698	959	1495	-	-	1488	-	-
Mov Cap-2 Maneuver	733	702	-	755	698	-	-	-	-	-	-	-
Stage 1	913	815	-	904	810	-	-	-	-	-	-	-
Stage 2	864	809	-	896	811	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.2		9.8			0.2			0.3			
HCM LOS	B		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1495	-	-	710	784	1488	-	-				
HCM Lane V/C Ratio	0.002	-	-	0.018	0.033	0.002	-	-				
HCM Control Delay (s)	7.4	0	-	10.2	9.8	7.4	0	-				
HCM Lane LOS	A	A	-	B	A	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.1	0.1	0	-	-				

Intersection												
Int Delay, s/veh	1.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	3	11	5	2	6	2	1	89	3	4	38	5
Future Vol, veh/h	3	11	5	2	6	2	1	89	3	4	38	5
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	0	0	0	0	0	0	0	0	0	0	0	0
Mvmt Flow	3	12	6	2	7	2	1	99	3	4	42	6
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	160	157	45	165	159	101	48	0	0	102	0	0
Stage 1	53	53	-	103	103	-	-	-	-	-	-	-
Stage 2	107	104	-	62	56	-	-	-	-	-	-	-
Critical Hdwy	7.1	6.5	6.2	7.1	6.5	6.2	4.1	-	-	4.1	-	-
Critical Hdwy Stg 1	6.1	5.5	-	6.1	5.5	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.1	5.5	-	6.1	5.5	-	-	-	-	-	-	-
Follow-up Hdwy	3.5	4	3.3	3.5	4	3.3	2.2	-	-	2.2	-	-
Pot Cap-1 Maneuver	810	739	1031	804	737	960	1572	-	-	1503	-	-
Stage 1	965	855	-	908	814	-	-	-	-	-	-	-
Stage 2	903	813	-	954	852	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	800	736	1031	787	734	960	1572	-	-	1503	-	-
Mov Cap-2 Maneuver	800	736	-	787	734	-	-	-	-	-	-	-
Stage 1	964	852	-	907	813	-	-	-	-	-	-	-
Stage 2	893	812	-	932	849	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s	9.6		9.7		0.1		0.6					
HCM LOS	A		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1572	-	-	807	781	1503	-	-				
HCM Lane V/C Ratio	0.001	-	-	0.026	0.014	0.003	-	-				
HCM Control Delay (s)	7.3	0	-	9.6	9.7	7.4	0	-				
HCM Lane LOS	A	A	-	A	A	A	A	-				
HCM 95th %tile O(veh)	0	-	-	0.1	0	0	-	-				

Intersection												
Int Delay, s/veh	3.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔			↔			↔			↔	
Traffic Vol, veh/h	23	13	13	1	16	23	8	102	2	10	95	17
Future Vol, veh/h	23	13	13	1	16	23	8	102	2	10	95	17
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	88	88	88	88	88	88	88	88	88	88	88	88
Heavy Vehicles, %	4	4	4	4	4	4	4	4	4	4	4	4
Mvmt Flow	26	15	15	1	18	26	9	116	2	11	108	19
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	297	276	118	290	284	117	127	0	0	118	0	0
Stage 1	140	140	-	135	135	-	-	-	-	-	-	-
Stage 2	157	136	-	155	149	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.14	6.54	6.24	4.14	-	-	4.14	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.14	5.54	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.536	4.036	3.336	2.236	-	-	2.236	-	-
Pot Cap-1 Maneuver	651	628	928	658	622	930	1447	-	-	1458	-	-
Stage 1	858	777	-	864	781	-	-	-	-	-	-	-
Stage 2	841	780	-	843	770	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	611	619	928	628	613	930	1447	-	-	1458	-	-
Mov Cap-2 Maneuver	611	619	-	628	613	-	-	-	-	-	-	-
Stage 1	852	771	-	858	776	-	-	-	-	-	-	-
Stage 2	793	775	-	807	764	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.8		10			0.5			0.6			
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1447	-	-	674	763	1458	-	-				
HCM Lane V/C Ratio	0.006	-	-	0.083	0.06	0.008	-	-				
HCM Control Delay (s)	7.5	0	-	10.8	10	7.5	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.3	0.2	0	-	-				

Intersection												
Int Delay, s/veh	3.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	16	15	16	2	13	22	17	119	3	14	57	28
Future Vol, veh/h	16	15	16	2	13	22	17	119	3	14	57	28
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	0	0	0	0	0	0	0	0	0	0	0	0
Mvmt Flow	18	17	18	2	14	24	19	132	3	16	63	31
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	302	284	79	300	298	134	94	0	0	135	0	0
Stage 1	111	111	-	172	172	-	-	-	-	-	-	-
Stage 2	191	173	-	128	126	-	-	-	-	-	-	-
Critical Hdwy	7.1	6.5	6.2	7.1	6.5	6.2	4.1	-	-	4.1	-	-
Critical Hdwy Stg 1	6.1	5.5	-	6.1	5.5	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.1	5.5	-	6.1	5.5	-	-	-	-	-	-	-
Follow-up Hdwy	3.5	4	3.3	3.5	4	3.3	2.2	-	-	2.2	-	-
Pot Cap-1 Maneuver	654	628	987	656	617	920	1513	-	-	1462	-	-
Stage 1	899	807	-	835	760	-	-	-	-	-	-	-
Stage 2	815	760	-	881	796	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	613	612	987	619	601	920	1513	-	-	1462	-	-
Mov Cap-2 Maneuver	613	612	-	619	601	-	-	-	-	-	-	-
Stage 1	886	797	-	823	749	-	-	-	-	-	-	-
Stage 2	767	749	-	837	786	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.5		10			0.9			1.1			
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1513	-	-	703	759	1462	-	-				
HCM Lane V/C Ratio	0.012	-	-	0.074	0.054	0.011	-	-				
HCM Control Delay (s)	7.4	0	-	10.5	10	7.5	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.2	0	-	-				

***MT. COMFORT ROAD & PROPOSED BROADVIEW
FARMS NORTH ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	3.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↰	↱			↰		↰	↱	↰	↱	↰	↱
Traffic Vol, veh/h	60	0	20	0	0	0	6	642	0	0	632	19
Future Vol, veh/h	60	0	20	0	0	0	6	642	0	0	632	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	0	-	-	-	-	-	100	-	405	135	-	100
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	65	0	22	0	0	0	7	698	0	0	687	21
Major/Minor	Minor2			Minor1			Major1			Major2		
Conflicting Flow All	1399	1399	687	1421	1420	698	708	0	0	698	0	0
Stage 1	687	687	-	712	712	-	-	-	-	-	-	-
Stage 2	712	712	-	709	708	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	118	141	447	114	136	440	891	-	-	898	-	-
Stage 1	437	447	-	423	436	-	-	-	-	-	-	-
Stage 2	423	436	-	425	438	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	117	140	447	108	135	440	891	-	-	898	-	-
Mov Cap-2 Maneuver	117	140	-	108	135	-	-	-	-	-	-	-
Stage 1	434	447	-	420	433	-	-	-	-	-	-	-
Stage 2	420	433	-	404	438	-	-	-	-	-	-	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	55.1			0			0.1			0		
HCM LOS	F			A								
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	EBLn2	WBLn1	SBL	SBT	SBR			
Capacity (veh/h)	891	-	-	117	447	-	898	-	-			
HCM Lane V/C Ratio	0.007	-	-	0.557	0.049	-	-	-	-			
HCM Control Delay (s)	9.1	-	-	69	13.5	0	0	-	-			
HCM Lane LOS	A	-	-	F	B	A	A	-	-			
HCM 95th %tile Q(veh)	0	-	-	2.7	0.2	-	0	-	-			

Intersection

Int Delay, s/veh 1.6

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↰	↱			↰↱		↰	↱	↰	↰	↱	↰
Traffic Vol, veh/h	40	0	12	0	0	0	19	580	0	0	605	70
Future Vol, veh/h	40	0	12	0	0	0	19	580	0	0	605	70
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	0	-	-	-	-	-	100	-	405	135	-	100
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	43	0	13	0	0	0	21	630	0	0	658	76

Major/Minor	Minor2		Minor1		Major1		Major2		Major2		Major2	
Conflicting Flow All	1330	1330	658	1375	1406	630	734	0	0	630	0	0
Stage 1	658	658	-	672	672	-	-	-	-	-	-	-
Stage 2	672	672	-	703	734	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	132	155	464	123	139	482	871	-	-	952	-	-
Stage 1	453	461	-	445	454	-	-	-	-	-	-	-
Stage 2	445	454	-	428	426	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	130	151	464	117	136	482	871	-	-	952	-	-
Mov Cap-2 Maneuver	130	151	-	117	136	-	-	-	-	-	-	-
Stage 1	442	461	-	434	443	-	-	-	-	-	-	-
Stage 2	434	443	-	416	426	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	38.4	0	0.3	0
HCM LOS	E	A		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	EBLn2	WBLn1	SBL	SBT	SBR
Capacity (veh/h)	871	-	-	130	464	-	952	-	-
HCM Lane V/C Ratio	0.024	-	-	0.334	0.028	-	-	-	-
HCM Control Delay (s)	9.2	-	-	46	13	0	0	-	-
HCM Lane LOS	A	-	-	E	B	A	A	-	-
HCM 95th %tile Q(veh)	0.1	-	-	1.3	0.1	-	0	-	-

***CR 750 N & McCORD STREET/PROPOSED
BROADVIEW FARMS ACCESS***

CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	1.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕		↕	↕			↕	
Traffic Vol, veh/h	0	182	5	11	249	0	17	0	29	0	0	0
Future Vol, veh/h	0	182	5	11	249	0	17	0	29	0	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	0	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	198	5	12	271	0	18	0	32	0	0	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	271	0	0	203	0	0	496	496	201	512	498	271
Stage 1	-	-	-	-	-	-	201	201	-	295	295	-
Stage 2	-	-	-	-	-	-	295	295	-	217	203	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1292	-	-	1369	-	-	484	475	840	472	474	768
Stage 1	-	-	-	-	-	-	801	735	-	713	669	-
Stage 2	-	-	-	-	-	-	713	669	-	785	733	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1292	-	-	1369	-	-	480	470	840	451	469	768
Mov Cap-2 Maneuver	-	-	-	-	-	-	480	470	-	451	469	-
Stage 1	-	-	-	-	-	-	801	735	-	713	662	-
Stage 2	-	-	-	-	-	-	706	662	-	756	733	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0			0.3			10.7			0		
HCM LOS							B			A		
Minor Lane/Major Mvmt	NBLn1		NBLn2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1		
Capacity (veh/h)	480		840	1292	-	-	1369	-	-	-		
HCM Lane V/C Ratio	0.038		0.038	-	-	-	0.009	-	-	-		
HCM Control Delay (s)	12.8		9.5	0	-	-	7.7	0	-	0		
HCM Lane LOS	B		A	A	-	-	A	A	-	A		
HCM 95th %tile Q(veh)	0.1		0.1	0	-	-	0	-	-	-		

Intersection												
Int Delay, s/veh	1.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔			↔		↔	↔			↔	
Traffic Vol, veh/h	0	245	16	29	169	0	11	2	16	0	3	0
Future Vol, veh/h	0	245	16	29	169	0	11	2	16	0	3	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	0	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	266	17	32	184	0	12	2	17	0	3	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	184	0	0	283	0	0	525	523	275	532	531	184
Stage 1	-	-	-	-	-	-	275	275	-	248	248	-
Stage 2	-	-	-	-	-	-	250	248	-	284	283	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1391	-	-	1279	-	-	463	459	764	458	454	858
Stage 1	-	-	-	-	-	-	731	683	-	756	701	-
Stage 2	-	-	-	-	-	-	754	701	-	723	677	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1391	-	-	1279	-	-	450	446	764	436	441	858
Mov Cap-2 Maneuver	-	-	-	-	-	-	450	446	-	436	441	-
Stage 1	-	-	-	-	-	-	731	683	-	756	681	-
Stage 2	-	-	-	-	-	-	729	681	-	704	677	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0			1.2			11.3			13.2		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1	NBLn2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1			
Capacity (veh/h)	450	708	1391	-	-	1279	-	-	441			
HCM Lane V/C Ratio	0.027	0.028	-	-	-	0.025	-	-	0.007			
HCM Control Delay (s)	13.2	10.2	0	-	-	7.9	0	-	13.2			
HCM Lane LOS	B	B	A	-	-	A	A	-	B			
HCM 95th %tile Q(veh)	0.1	0.1	0	-	-	0.1	-	-	0			

***CR 750 N & PROPOSED MCCORD SQUARE EAST
ACCESS DRIVE/PROPOSED COLONNADE EAST
ACCESS DRIVE
CAPACITY ANALYSIS***

Intersection

Int Delay, s/veh 2.1

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕		↕	↕		↕	↕	
Traffic Vol, veh/h	15	102	3	2	162	5	9	7	6	3	3	31
Future Vol, veh/h	15	102	3	2	162	5	9	7	6	3	3	31
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	100	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	16	111	3	2	176	5	10	8	7	3	3	34

Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	181	0	0	114	0	0	346	330	113	335	329	179
Stage 1	-	-	-	-	-	-	145	145	-	183	183	-
Stage 2	-	-	-	-	-	-	201	185	-	152	146	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1394	-	-	1475	-	-	608	589	940	619	590	864
Stage 1	-	-	-	-	-	-	858	777	-	819	748	-
Stage 2	-	-	-	-	-	-	801	747	-	850	776	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1394	-	-	1475	-	-	576	581	940	602	582	864
Mov Cap-2 Maneuver	-	-	-	-	-	-	576	581	-	602	582	-
Stage 1	-	-	-	-	-	-	848	768	-	809	747	-
Stage 2	-	-	-	-	-	-	765	746	-	826	767	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	1	0.1	10.7	9.6
HCM LOS			B	A

Minor Lane/Major Mvmt	NBLn1	NBLn2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	576	705	1394	-	-	1475	-	-	602	829
HCM Lane V/C Ratio	0.017	0.02	0.012	-	-	0.001	-	-	0.005	0.045
HCM Control Delay (s)	11.4	10.2	7.6	0	-	7.4	0	-	11	9.5
HCM Lane LOS	B	B	A	A	-	A	A	-	B	A
HCM 95th %tile Q(veh)	0.1	0.1	0	-	-	0	-	-	0	0.1

Intersection												
Int Delay, s/veh	2.2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔			↔		↔	↔		↔	↔	
Traffic Vol, veh/h	35	178	10	8	114	5	6	5	4	3	8	26
Future Vol, veh/h	35	178	10	8	114	5	6	5	4	3	8	26
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	100	-	-	100	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	38	193	11	9	124	5	7	5	4	3	9	28
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	129	0	0	204	0	0	438	422	199	424	425	127
Stage 1	-	-	-	-	-	-	275	275	-	145	145	-
Stage 2	-	-	-	-	-	-	163	147	-	279	280	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1457	-	-	1368	-	-	529	523	842	540	521	923
Stage 1	-	-	-	-	-	-	731	683	-	858	777	-
Stage 2	-	-	-	-	-	-	839	775	-	728	679	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1457	-	-	1368	-	-	492	504	842	518	502	923
Mov Cap-2 Maneuver	-	-	-	-	-	-	492	504	-	518	502	-
Stage 1	-	-	-	-	-	-	710	663	-	833	772	-
Stage 2	-	-	-	-	-	-	799	770	-	697	659	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	1.2			0.5			11.6			10.1		
HCM LOS							B			B		
Minor Lane/Major Mvmt	NBLn1		NBLn2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1	SBLn2	
Capacity (veh/h)	492		613	1457	-	-	1368	-	-	518	771	
HCM Lane V/C Ratio	0.013		0.016	0.026	-	-	0.006	-	-	0.006	0.048	
HCM Control Delay (s)	12.4		11	7.5	0	-	7.6	0	-	12	9.9	
HCM Lane LOS	B		B	A	A	-	A	A	-	B	A	
HCM 95th %tile Q(veh)	0		0	0.1	-	-	0	-	-	0	0.2	

Intersection				
Intersection Delay, s/veh	3.7			
Intersection LOS	A			
Approach	EB	WB	NB	SB
Entry Lanes	1	1	1	1
Conflicting Circle Lanes	1	1	1	1
Adj Approach Flow, veh/h	130	183	25	40
Demand Flow Rate, veh/h	132	187	25	41
Vehicles Circulating, veh/h	8	34	132	192
Vehicles Exiting, veh/h	225	123	8	29
Ped Vol Crossing Leg, #/h	0	0	0	0
Ped Cap Adj	1.000	1.000	1.000	1.000
Approach Delay, s/veh	3.4	3.9	3.2	3.6
Approach LOS	A	A	A	A
Lane	Left	Left	Left	Left
Designated Moves	LTR	LTR	LTR	LTR
Assumed Moves	LTR	LTR	LTR	LTR
RT Channelized				
Lane Util	1.000	1.000	1.000	1.000
Follow-Up Headway, s	2.609	2.609	2.609	2.609
Critical Headway, s	4.976	4.976	4.976	4.976
Entry Flow, veh/h	132	187	25	41
Cap Entry Lane, veh/h	1369	1333	1206	1134
Entry HV Adj Factor	0.983	0.981	0.994	0.974
Flow Entry, veh/h	130	183	25	40
Cap Entry, veh/h	1346	1308	1198	1105
V/C Ratio	0.096	0.140	0.021	0.036
Control Delay, s/veh	3.4	3.9	3.2	3.6
LOS	A	A	A	A
95th %tile Queue, veh	0	0	0	0

Intersection				
Intersection Delay, s/veh	4.0			
Intersection LOS	A			
Approach	EB	WB	NB	SB
Entry Lanes	1	1	1	1
Conflicting Circle Lanes	1	1	1	1
Adj Approach Flow, veh/h	242	138	16	40
Demand Flow Rate, veh/h	247	140	16	41
Vehicles Circulating, veh/h	21	51	239	142
Vehicles Exiting, veh/h	162	204	29	49
Ped Vol Crossing Leg, #/h	0	0	0	0
Ped Cap Adj	1.000	1.000	1.000	1.000
Approach Delay, s/veh	4.2	3.7	3.5	3.4
Approach LOS	A	A	A	A
Lane	Left	Left	Left	Left
Designated Moves	LTR	LTR	LTR	LTR
Assumed Moves	LTR	LTR	LTR	LTR
RT Channelized				
Lane Util	1.000	1.000	1.000	1.000
Follow-Up Headway, s	2.609	2.609	2.609	2.609
Critical Headway, s	4.976	4.976	4.976	4.976
Entry Flow, veh/h	247	140	16	41
Cap Entry Lane, veh/h	1351	1310	1081	1194
Entry HV Adj Factor	0.980	0.982	0.994	0.971
Flow Entry, veh/h	242	138	16	40
Cap Entry, veh/h	1324	1287	1075	1160
V/C Ratio	0.183	0.107	0.015	0.034
Control Delay, s/veh	4.2	3.7	3.5	3.4
LOS	A	A	A	A
95th %tile Queue, veh	1	0	0	0

***CR 750 N & PROPOSED McCORD SQUARE WEST
ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection						
Int Delay, s/veh	1.6					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	↕
Traffic Vol, veh/h	39	119	245	14	9	34
Future Vol, veh/h	39	119	245	14	9	34
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	42	129	266	15	10	37
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	281	0	-	0	487	274
Stage 1	-	-	-	-	274	-
Stage 2	-	-	-	-	213	-
Critical Hdwy	4.12	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	1282	-	-	-	540	765
Stage 1	-	-	-	-	772	-
Stage 2	-	-	-	-	823	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	1282	-	-	-	521	765
Mov Cap-2 Maneuver	-	-	-	-	521	-
Stage 1	-	-	-	-	745	-
Stage 2	-	-	-	-	823	-
Approach	EB	WB		SB		
HCM Control Delay, s	2	0		10.3		
HCM LOS	B					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1282	-	-	-	521	765
HCM Lane V/C Ratio	0.033	-	-	-	0.019	0.048
HCM Control Delay (s)	7.9	0	-	-	12	9.9
HCM Lane LOS	A	A	-	-	B	A
HCM 95th %tile Q(veh)	0.1	-	-	-	0.1	0.2

Intersection						
Int Delay, s/veh	2					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	↕
Traffic Vol, veh/h	47	246	161	16	16	56
Future Vol, veh/h	47	246	161	16	16	56
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	51	267	175	17	17	61
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	192	0	-	0	553	184
Stage 1	-	-	-	-	184	-
Stage 2	-	-	-	-	369	-
Critical Hdwy	4.12	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	1381	-	-	-	494	858
Stage 1	-	-	-	-	848	-
Stage 2	-	-	-	-	699	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	1381	-	-	-	473	858
Mov Cap-2 Maneuver	-	-	-	-	473	-
Stage 1	-	-	-	-	812	-
Stage 2	-	-	-	-	699	-
Approach	EB	WB		SB		
HCM Control Delay, s	1.2	0		10.3		
HCM LOS				B		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1381	-	-	-	473	858
HCM Lane V/C Ratio	0.037	-	-	-	0.037	0.071
HCM Control Delay (s)	7.7	0	-	-	12.9	9.5
HCM Lane LOS	A	A	-	-	B	A
HCM 95th %tile Q(veh)	0.1	-	-	-	0.1	0.2

***CR 750 N & PROPOSED McCORD SQUARE
TOWNHOME ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection

Int Delay, s/veh 0.4

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↰	↰		↰	↰
Traffic Vol, veh/h	4	154	277	1	4	12
Future Vol, veh/h	4	154	277	1	4	12
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	4	167	301	1	4	13

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	302	0	0 477 302
Stage 1	-	-	- 302 -
Stage 2	-	-	- 175 -
Critical Hdwy	4.12	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.218	-	- 3.518 3.318
Pot Cap-1 Maneuver	1259	-	- 547 738
Stage 1	-	-	- 750 -
Stage 2	-	-	- 855 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1259	-	- 545 738
Mov Cap-2 Maneuver	-	-	- 545 -
Stage 1	-	-	- 747 -
Stage 2	-	-	- 855 -

Approach	EB	WB	SB
HCM Control Delay, s	0.2	0	10.4
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1259	-	-	-	545	738
HCM Lane V/C Ratio	0.003	-	-	-	0.008	0.018
HCM Control Delay (s)	7.9	0	-	-	11.7	10
HCM Lane LOS	A	A	-	-	B	B
HCM 95th %tile Q(veh)	0	-	-	-	0	0.1

Intersection

Int Delay, s/veh 0.2

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↰	↰		↰	↰
Traffic Vol, veh/h	8	291	213	3	1	5
Future Vol, veh/h	8	291	213	3	1	5
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	9	316	232	3	1	5

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	235	0	568
Stage 1	-	-	234
Stage 2	-	-	334
Critical Hdwy	4.12	-	6.42
Critical Hdwy Stg 1	-	-	5.42
Critical Hdwy Stg 2	-	-	5.42
Follow-up Hdwy	2.218	-	3.518
Pot Cap-1 Maneuver	1332	-	484
Stage 1	-	-	805
Stage 2	-	-	725
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1332	-	480
Mov Cap-2 Maneuver	-	-	480
Stage 1	-	-	799
Stage 2	-	-	725

Approach	EB	WB	SB
HCM Control Delay, s	0.2	0	10
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1332	-	-	-	480	805
HCM Lane V/C Ratio	0.007	-	-	-	0.002	0.007
HCM Control Delay (s)	7.7	0	-	-	12.5	9.5
HCM Lane LOS	A	A	-	-	B	A
HCM 95th %tile Q(veh)	0	-	-	-	0	0

***BROADWAY & PROPOSED McCORD SQUARE WEST
ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection						
Int Delay, s/veh	0.4					
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations						
Traffic Vol, veh/h	6	14	694	5	13	689
Future Vol, veh/h	6	14	694	5	13	689
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	-	-	355	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	7	15	754	5	14	749
Major/Minor	Minor1	Major1	Major2			
Conflicting Flow All	1160	380	0	0	759	0
Stage 1	757	-	-	-	-	-
Stage 2	403	-	-	-	-	-
Critical Hdwy	6.84	6.94	-	-	4.14	-
Critical Hdwy Stg 1	5.84	-	-	-	-	-
Critical Hdwy Stg 2	5.84	-	-	-	-	-
Follow-up Hdwy	3.52	3.32	-	-	2.22	-
Pot Cap-1 Maneuver	189	618	-	-	848	-
Stage 1	424	-	-	-	-	-
Stage 2	644	-	-	-	-	-
Platoon blocked, %			-	-	-	-
Mov Cap-1 Maneuver	184	618	-	-	848	-
Mov Cap-2 Maneuver	184	-	-	-	-	-
Stage 1	424	-	-	-	-	-
Stage 2	626	-	-	-	-	-
Approach	NW	NE	SW			
HCM Control Delay, s	15.3	0	0.3			
HCM LOS	C					
Minor Lane/Major Mvmt	NET	NER	NWL	N1NWL	N2	SWL SWT
Capacity (veh/h)	-	-	184	618	848	-
HCM Lane V/C Ratio	-	-	0.035	0.025	0.017	-
HCM Control Delay (s)	-	-	25.3	11	9.3	0.1
HCM Lane LOS	-	-	D	B	A	A
HCM 95th %tile Q(veh)	-	-	0.1	0.1	0.1	-

Intersection

Int Delay, s/veh 0.8

Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations						
Traffic Vol, veh/h	10	26	1183	18	19	724
Future Vol, veh/h	10	26	1183	18	19	724
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	-	-	355	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	11	28	1286	20	21	787

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	1732	653	0
Stage 1	1296	-	-
Stage 2	436	-	-
Critical Hdwy	6.84	6.94	-
Critical Hdwy Stg 1	5.84	-	-
Critical Hdwy Stg 2	5.84	-	-
Follow-up Hdwy	3.52	3.32	-
Pot Cap-1 Maneuver	79	410	-
Stage 1	220	-	-
Stage 2	619	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	73	410	-
Mov Cap-2 Maneuver	73	-	-
Stage 1	220	-	-
Stage 2	575	-	-

Approach	NW	NE	SW
HCM Control Delay, s	27.8	0	0.7
HCM LOS	D		

Minor Lane/Major Mvmt	NET	NER	NWL	N1	NWL	N2	SWL	SWT
Capacity (veh/h)	-	-	73	410	526	-	-	-
HCM Lane V/C Ratio	-	-	0.149	0.069	0.039	-	-	-
HCM Control Delay (s)	-	-	62.8	14.4	12.1	0.4	-	-
HCM Lane LOS	-	-	F	B	B	A	-	-
HCM 95th %tile Q(veh)	-	-	0.5	0.2	0.1	-	-	-

***BROADWAY & PROPOSED McCORD SQUARE EAST
ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection						
Int Delay, s/veh	3.6					
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations	↰	↰	↰↰	↰	↰	↰
Traffic Vol, veh/h	64	47	626	82	46	639
Future Vol, veh/h	64	47	626	82	46	639
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	-	100	100	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	70	51	680	89	50	695
Major/Minor	Minor1	Major1	Major2			
Conflicting Flow All	1475	340	0	0	769	0
Stage 1	680	-	-	-	-	-
Stage 2	795	-	-	-	-	-
Critical Hdwy	6.63	6.93	-	-	4.13	-
Critical Hdwy Stg 1	5.83	-	-	-	-	-
Critical Hdwy Stg 2	5.43	-	-	-	-	-
Follow-up Hdwy	3.519	3.319	-	-	2.219	-
Pot Cap-1 Maneuver	128	657	-	-	843	-
Stage 1	466	-	-	-	-	-
Stage 2	444	-	-	-	-	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	120	657	-	-	843	-
Mov Cap-2 Maneuver	120	-	-	-	-	-
Stage 1	466	-	-	-	-	-
Stage 2	418	-	-	-	-	-
Approach	NW	NE	SW			
HCM Control Delay, s	44.9	0	0.6			
HCM LOS	E					
Minor Lane/Major Mvmt	NET	NER	NWL	N1NWL	N2	SWL SWT
Capacity (veh/h)	-	-	120	657	843	-
HCM Lane V/C Ratio	-	-	0.58	0.078	0.059	-
HCM Control Delay (s)	-	-	69.9	10.9	9.5	-
HCM Lane LOS	-	-	F	B	A	-
HCM 95th %tile Q(veh)	-	-	2.9	0.3	0.2	-

Intersection						
Int Delay, s/veh	41.6					
Movement	NWL	NWR	NET	NER	SWL	SWT
Lane Configurations	↰	↰	↰↰	↰	↰	↰
Traffic Vol, veh/h	104	89	1079	131	76	639
Future Vol, veh/h	104	89	1079	131	76	639
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	-	100	100	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	113	97	1173	142	83	695
Major/Minor	Minor1	Major1	Major2			
Conflicting Flow All	2034	587	0	0	1315	0
Stage 1	1173	-	-	-	-	-
Stage 2	861	-	-	-	-	-
Critical Hdwy	6.63	6.93	-	-	4.13	-
Critical Hdwy Stg 1	5.83	-	-	-	-	-
Critical Hdwy Stg 2	5.43	-	-	-	-	-
Follow-up Hdwy	3.519	3.319	-	-	2.219	-
Pot Cap-1 Maneuver	~ 56	454	-	-	524	-
Stage 1	257	-	-	-	-	-
Stage 2	413	-	-	-	-	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	~ 47	454	-	-	524	-
Mov Cap-2 Maneuver	~ 47	-	-	-	-	-
Stage 1	257	-	-	-	-	-
Stage 2	348	-	-	-	-	-
Approach	NW	NE	SW			
HCM Control Delay, s	451.7	0	1.4			
HCM LOS	F					
Minor Lane/Major Mvmt	NET	NER	NWLn1	NWLn2	SWL	SWT
Capacity (veh/h)	-	-	47	454	524	-
HCM Lane V/C Ratio	-	-	2.405	0.213	0.158	-
HCM Control Delay (s)	-	-	\$ 825.4	15.1	13.2	-
HCM Lane LOS	-	-	F	C	B	-
HCM 95th %tile Q(veh)	-	-	11.8	0.8	0.6	-
Notes						
~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon						

***SR 234 & PROPOSED McCORD SQUARE ACCESS
DRIVE***

CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	1.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔		↔	↔		↔	↔		↔	↔	
Traffic Vol, veh/h	0	283	6	31	275	0	9	0	32	0	0	0
Future Vol, veh/h	0	283	6	31	275	0	9	0	32	0	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	100	-	-	100	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	308	7	34	299	0	10	0	35	0	0	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	299	0	0	315	0	0	679	679	312	696	682	299
Stage 1	-	-	-	-	-	-	312	312	-	367	367	-
Stage 2	-	-	-	-	-	-	367	367	-	329	315	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1262	-	-	1245	-	-	366	374	728	356	372	741
Stage 1	-	-	-	-	-	-	699	658	-	653	622	-
Stage 2	-	-	-	-	-	-	653	622	-	684	656	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1262	-	-	1245	-	-	358	364	728	332	362	741
Mov Cap-2 Maneuver	-	-	-	-	-	-	358	364	-	332	362	-
Stage 1	-	-	-	-	-	-	699	658	-	653	605	-
Stage 2	-	-	-	-	-	-	635	605	-	651	656	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0			0.8			11.3			0		
HCM LOS							B			A		
Minor Lane/Major Mvmt	NBLn1		NBLn2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1		
Capacity (veh/h)	358		728	1262	-	-	1245	-	-	-		
HCM Lane V/C Ratio	0.027		0.048	-	-	-	0.027	-	-	-		
HCM Control Delay (s)	15.3		10.2	0	-	-	8	-	-	0		
HCM Lane LOS	C		B	A	-	-	A	-	-	A		
HCM 95th %tile Q(veh)	0.1		0.1	0	-	-	0.1	-	-	-		

Intersection												
Int Delay, s/veh	1.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔		↔	↔		↔	↔			↔	
Traffic Vol, veh/h	0	233	14	43	276	0	9	0	34	0	0	0
Future Vol, veh/h	0	233	14	43	276	0	9	0	34	0	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	100	-	-	100	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	253	15	47	300	0	10	0	37	0	0	0
Major/Minor	Major1			Major2			Minor1			Minor2		
Conflicting Flow All	300	0	0	268	0	0	655	655	261	673	662	300
Stage 1	-	-	-	-	-	-	261	261	-	394	394	-
Stage 2	-	-	-	-	-	-	394	394	-	279	268	-
Critical Hdwy	4.12	-	-	4.12	-	-	7.12	6.52	6.22	7.12	6.52	6.22
Critical Hdwy Stg 1	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Critical Hdwy Stg 2	-	-	-	-	-	-	6.12	5.52	-	6.12	5.52	-
Follow-up Hdwy	2.218	-	-	2.218	-	-	3.518	4.018	3.318	3.518	4.018	3.318
Pot Cap-1 Maneuver	1261	-	-	1296	-	-	379	386	778	369	382	740
Stage 1	-	-	-	-	-	-	744	692	-	631	605	-
Stage 2	-	-	-	-	-	-	631	605	-	728	687	-
Platoon blocked, %	-	-	-	-	-	-	-	-	-	-	-	-
Mov Cap-1 Maneuver	1261	-	-	1296	-	-	368	372	778	342	368	740
Mov Cap-2 Maneuver	-	-	-	-	-	-	368	372	-	342	368	-
Stage 1	-	-	-	-	-	-	744	692	-	631	583	-
Stage 2	-	-	-	-	-	-	608	583	-	693	687	-
Approach	EB			WB			NB			SB		
HCM Control Delay, s	0			1.1			11			0		
HCM LOS							B			A		
Minor Lane/Major Mvmt	NBLn1		NBLn2	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1		
Capacity (veh/h)	368		778	1261	-	-	1296	-	-	-		
HCM Lane V/C Ratio	0.027		0.048	-	-	-	0.036	-	-	-		
HCM Control Delay (s)	15.1		9.9	0	-	-	7.9	-	-	0		
HCM Lane LOS	C		A	A	-	-	A	-	-	A		
HCM 95th %tile Q(veh)	0.1		0.1	0	-	-	0.1	-	-	-		

***CR 700 N & PROPOSED COLONNADE ACCESS
DRIVE***

CAPACITY ANALYSIS

Intersection

Int Delay, s/veh 4.2

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↰	↰		↰	↰
Traffic Vol, veh/h	18	31	34	6	19	34
Future Vol, veh/h	18	31	34	6	19	34
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	20	34	37	7	21	37

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	44	0	115
Stage 1	-	-	41
Stage 2	-	-	74
Critical Hdwy	4.12	-	6.42
Critical Hdwy Stg 1	-	-	5.42
Critical Hdwy Stg 2	-	-	5.42
Follow-up Hdwy	2.218	-	3.518
Pot Cap-1 Maneuver	1564	-	881
Stage 1	-	-	981
Stage 2	-	-	949
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1564	-	870
Mov Cap-2 Maneuver	-	-	870
Stage 1	-	-	968
Stage 2	-	-	949

Approach	EB	WB	SB
HCM Control Delay, s	2.7	0	8.8
HCM LOS			A

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1564	-	-	-	870	1030
HCM Lane V/C Ratio	0.013	-	-	-	0.024	0.036
HCM Control Delay (s)	7.3	0	-	-	9.2	8.6
HCM Lane LOS	A	A	-	-	A	A
HCM 95th %tile Q(veh)	0	-	-	-	0.1	0.1

Intersection

Int Delay, s/veh 4.2

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↰	↰		↰	↰
Traffic Vol, veh/h	61	34	35	21	13	23
Future Vol, veh/h	61	34	35	21	13	23
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	66	37	38	23	14	25

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	61	0	0 219 50
Stage 1	-	-	- 50 -
Stage 2	-	-	- 169 -
Critical Hdwy	4.12	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.218	-	- 3.518 3.318
Pot Cap-1 Maneuver	1542	-	- 769 1018
Stage 1	-	-	- 972 -
Stage 2	-	-	- 861 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1542	-	- 735 1018
Mov Cap-2 Maneuver	-	-	- 735 -
Stage 1	-	-	- 929 -
Stage 2	-	-	- 861 -

Approach	EB	WB	SB
HCM Control Delay, s	4.8	0	9.1
HCM LOS			A

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1542	-	-	-	735	1018
HCM Lane V/C Ratio	0.043	-	-	-	0.019	0.025
HCM Control Delay (s)	7.4	0	-	-	10	8.6
HCM Lane LOS	A	A	-	-	B	A
HCM 95th %tile Q(veh)	0.1	-	-	-	0.1	0.1

***CR 750 N & PROPOSED COLONNADE WEST
ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection

Int Delay, s/veh 1.8

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	116	13	1	201	58	5
Future Vol, veh/h	116	13	1	201	58	5
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	126	14	1	218	63	5

Major/Minor	Major1	Major2	Minor1
Conflicting Flow All	0	0	140
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	-	4.12	-
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	-	2.218	-
Pot Cap-1 Maneuver	-	1443	-
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	1443	-
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	NB
HCM Control Delay, s	0	0	11
HCM LOS			B

Minor Lane/Major Mvmt	NBLn1	NBLn2	EBT	EBR	WBL	WBT
Capacity (veh/h)	644	916	-	-	1443	-
HCM Lane V/C Ratio	0.098	0.006	-	-	0.001	-
HCM Control Delay (s)	11.2	9	-	-	7.5	0
HCM Lane LOS	B	A	-	-	A	A
HCM 95th %tile Q(veh)	0.3	0	-	-	0	-

Intersection

Int Delay, s/veh 1.1

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	220	43	4	141	37	3
Future Vol, veh/h	220	43	4	141	37	3
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	239	47	4	153	40	3

Major/Minor	Major1	Major2	Minor1
Conflicting Flow All	0	0	286
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	-	-	4.12
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	-	-	2.218
Pot Cap-1 Maneuver	-	-	1276
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	1276
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	NB
HCM Control Delay, s	0	0.2	11.5
HCM LOS			B

Minor Lane/Major Mvmt	NBLn1	NBLn2	EBT	EBR	WBL	WBT
Capacity (veh/h)	585	776	-	-	1276	-
HCM Lane V/C Ratio	0.069	0.004	-	-	0.003	-
HCM Control Delay (s)	11.6	9.7	-	-	7.8	0
HCM Lane LOS	B	A	-	-	A	A
HCM 95th %tile Q(veh)	0.2	0	-	-	0	-

***CR 750 N & PROPOSED JACOBI LEGACY FARMS
WEST ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection						
Int Delay, s/veh	1.9					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	14	97	125	2	3	44
Future Vol, veh/h	14	97	125	2	3	44
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	15	105	136	2	3	48
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	138	0	-	0	272	137
Stage 1	-	-	-	-	137	-
Stage 2	-	-	-	-	135	-
Critical Hdwy	4.12	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	1446	-	-	-	717	911
Stage 1	-	-	-	-	890	-
Stage 2	-	-	-	-	891	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	1446	-	-	-	709	911
Mov Cap-2 Maneuver	-	-	-	-	709	-
Stage 1	-	-	-	-	880	-
Stage 2	-	-	-	-	891	-
Approach	EB	WB		SB		
HCM Control Delay, s	0.9	0		9.3		
HCM LOS	A					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1446	-	-	-	709	911
HCM Lane V/C Ratio	0.011	-	-	-	0.005	0.052
HCM Control Delay (s)	7.5	0	-	-	10.1	9.2
HCM Lane LOS	A	A	-	-	B	A
HCM 95th %tile Q(veh)	0	-	-	-	0	0.2

Intersection

Int Delay, s/veh 2

Movement	EBL	EBT	WBT	WBR	SBL	SBR
----------	-----	-----	-----	-----	-----	-----

Lane Configurations		↰	↰		↰	↰
---------------------	--	---	---	--	---	---

Traffic Vol, veh/h	47	137	101	7	3	28
--------------------	----	-----	-----	---	---	----

Future Vol, veh/h	47	137	101	7	3	28
-------------------	----	-----	-----	---	---	----

Conflicting Peds, #/hr	0	0	0	0	0	0
------------------------	---	---	---	---	---	---

Sign Control	Free	Free	Free	Free	Stop	Stop
--------------	------	------	------	------	------	------

RT Channelized	-	None	-	None	-	None
----------------	---	------	---	------	---	------

Storage Length	-	-	-	-	0	0
----------------	---	---	---	---	---	---

Veh in Median Storage, #	-	0	0	-	0	-
--------------------------	---	---	---	---	---	---

Grade, %	-	0	0	-	0	-
----------	---	---	---	---	---	---

Peak Hour Factor	92	92	92	92	92	92
------------------	----	----	----	----	----	----

Heavy Vehicles, %	2	2	2	2	2	2
-------------------	---	---	---	---	---	---

Mvmt Flow	51	149	110	8	3	30
-----------	----	-----	-----	---	---	----

Major/Minor	Major1	Major2	Minor2
-------------	--------	--------	--------

Conflicting Flow All	118	0	0	365	114
----------------------	-----	---	---	-----	-----

Stage 1	-	-	-	114	-
---------	---	---	---	-----	---

Stage 2	-	-	-	251	-
---------	---	---	---	-----	---

Critical Hdwy	4.12	-	-	6.42	6.22
---------------	------	---	---	------	------

Critical Hdwy Stg 1	-	-	-	5.42	-
---------------------	---	---	---	------	---

Critical Hdwy Stg 2	-	-	-	5.42	-
---------------------	---	---	---	------	---

Follow-up Hdwy	2.218	-	-	3.518	3.318
----------------	-------	---	---	-------	-------

Pot Cap-1 Maneuver	1470	-	-	635	939
--------------------	------	---	---	-----	-----

Stage 1	-	-	-	911	-
---------	---	---	---	-----	---

Stage 2	-	-	-	791	-
---------	---	---	---	-----	---

Platoon blocked, %	-	-	-	-	-
--------------------	---	---	---	---	---

Mov Cap-1 Maneuver	1470	-	-	611	939
--------------------	------	---	---	-----	-----

Mov Cap-2 Maneuver	-	-	-	611	-
--------------------	---	---	---	-----	---

Stage 1	-	-	-	876	-
---------	---	---	---	-----	---

Stage 2	-	-	-	791	-
---------	---	---	---	-----	---

Approach	EB	WB	SB
----------	----	----	----

HCM Control Delay, s	1.9	0	9.2
----------------------	-----	---	-----

HCM LOS			A
---------	--	--	---

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
-----------------------	-----	-----	-----	-----	-------	-------

Capacity (veh/h)	1470	-	-	-	611	939
------------------	------	---	---	---	-----	-----

HCM Lane V/C Ratio	0.035	-	-	-	0.005	0.032
--------------------	-------	---	---	---	-------	-------

HCM Control Delay (s)	7.5	0	-	-	10.9	9
-----------------------	-----	---	---	---	------	---

HCM Lane LOS	A	A	-	-	B	A
--------------	---	---	---	---	---	---

HCM 95th %tile Q(veh)	0.1	-	-	-	0	0.1
-----------------------	-----	---	---	---	---	-----

***CR 750 N & PROPOSED JACOBI LEGACY FARMS
MAIN ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection

Int Delay, s/veh 2.5

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↰	↰		↰	↰
Traffic Vol, veh/h	14	86	81	4	10	46
Future Vol, veh/h	14	86	81	4	10	46
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	15	93	88	4	11	50

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	92	0	0 213 90
Stage 1	-	-	- 90 -
Stage 2	-	-	- 123 -
Critical Hdwy	4.12	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.218	-	- 3.518 3.318
Pot Cap-1 Maneuver	1503	-	- 775 968
Stage 1	-	-	- 934 -
Stage 2	-	-	- 902 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1503	-	- 766 968
Mov Cap-2 Maneuver	-	-	- 766 -
Stage 1	-	-	- 924 -
Stage 2	-	-	- 902 -

Approach	EB	WB	SB
HCM Control Delay, s	1	0	9.1
HCM LOS			A

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1503	-	-	-	766	968
HCM Lane V/C Ratio	0.01	-	-	-	0.014	0.052
HCM Control Delay (s)	7.4	0	-	-	9.8	8.9
HCM Lane LOS	A	A	-	-	A	A
HCM 95th %tile Q(veh)	0	-	-	-	0	0.2

Intersection						
Int Delay, s/veh	2.6					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	49	91	80	12	7	28
Future Vol, veh/h	49	91	80	12	7	28
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	53	99	87	13	8	30
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	100	0	-	0	299	94
Stage 1	-	-	-	-	94	-
Stage 2	-	-	-	-	205	-
Critical Hdwy	4.12	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	1493	-	-	-	692	963
Stage 1	-	-	-	-	930	-
Stage 2	-	-	-	-	829	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	1493	-	-	-	666	963
Mov Cap-2 Maneuver	-	-	-	-	666	-
Stage 1	-	-	-	-	895	-
Stage 2	-	-	-	-	829	-
Approach	EB	WB		SB		
HCM Control Delay, s	2.6	0		9.2		
HCM LOS				A		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1493	-	-	-	666	963
HCM Lane V/C Ratio	0.036	-	-	-	0.011	0.032
HCM Control Delay (s)	7.5	0	-	-	10.5	8.9
HCM Lane LOS	A	A	-	-	B	A
HCM 95th %tile Q(veh)	0.1	-	-	-	0	0.1

***CR 750 N & PROPOSED JACOBI LEGACY FARMS
EAST ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection

Int Delay, s/veh 1.7

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↰	↰		↰	↰
Traffic Vol, veh/h	7	90	64	4	12	20
Future Vol, veh/h	7	90	64	4	12	20
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	8	98	70	4	13	22

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	74	0	0 186 72
Stage 1	-	-	- 72 -
Stage 2	-	-	- 114 -
Critical Hdwy	4.12	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.218	-	- 3.518 3.318
Pot Cap-1 Maneuver	1526	-	- 803 990
Stage 1	-	-	- 951 -
Stage 2	-	-	- 911 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1526	-	- 798 990
Mov Cap-2 Maneuver	-	-	- 798 -
Stage 1	-	-	- 945 -
Stage 2	-	-	- 911 -

Approach	EB	WB	SB
HCM Control Delay, s	0.5	0	9
HCM LOS			A

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1526	-	-	-	798	990
HCM Lane V/C Ratio	0.005	-	-	-	0.016	0.022
HCM Control Delay (s)	7.4	0	-	-	9.6	8.7
HCM Lane LOS	A	A	-	-	A	A
HCM 95th %tile Q(veh)	0	-	-	-	0.1	0.1

Intersection						
Int Delay, s/veh	1.6					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	21	78	88	15	8	13
Future Vol, veh/h	21	78	88	15	8	13
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	0
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	23	85	96	16	9	14
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	112	0	-	0	235	104
Stage 1	-	-	-	-	104	-
Stage 2	-	-	-	-	131	-
Critical Hdwy	4.12	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	1478	-	-	-	753	951
Stage 1	-	-	-	-	920	-
Stage 2	-	-	-	-	895	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	1478	-	-	-	741	951
Mov Cap-2 Maneuver	-	-	-	-	741	-
Stage 1	-	-	-	-	905	-
Stage 2	-	-	-	-	895	-
Approach	EB		WB		SB	
HCM Control Delay, s	1.6		0		9.2	
HCM LOS					A	
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	SBLn2
Capacity (veh/h)	1478	-	-	-	741	951
HCM Lane V/C Ratio	0.015	-	-	-	0.012	0.015
HCM Control Delay (s)	7.5	0	-	-	9.9	8.8
HCM Lane LOS	A	A	-	-	A	A
HCM 95th %tile Q(veh)	0	-	-	-	0	0

***CR 500 W & PROPOSED JACOBI LEGACY FARMS
ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection						
Int Delay, s/veh	1.6					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	35	14	8	178	114	11
Future Vol, veh/h	35	14	8	178	114	11
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	100	0	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	38	15	9	193	124	12
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	341	130	136	0	-	0
Stage 1	130	-	-	-	-	-
Stage 2	211	-	-	-	-	-
Critical Hdwy	6.42	6.22	4.12	-	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	2.218	-	-	-
Pot Cap-1 Maneuver	655	920	1448	-	-	-
Stage 1	896	-	-	-	-	-
Stage 2	824	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	650	920	1448	-	-	-
Mov Cap-2 Maneuver	650	-	-	-	-	-
Stage 1	890	-	-	-	-	-
Stage 2	824	-	-	-	-	-
Approach	EB		NB		SB	
HCM Control Delay, s	10.4		0.3		0	
HCM LOS	B					
Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	1448	-	650	920	-	-
HCM Lane V/C Ratio	0.006	-	0.059	0.017	-	-
HCM Control Delay (s)	7.5	0	10.9	9	-	-
HCM Lane LOS	A	A	B	A	-	-
HCM 95th %tile Q(veh)	0	-	0.2	0.1	-	-

Intersection						
Int Delay, s/veh	1.5					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	25	10	20	139	130	31
Future Vol, veh/h	25	10	20	139	130	31
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	100	0	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	27	11	22	151	141	34
Major/Minor	Minor2	Major1		Major2		
Conflicting Flow All	353	158	175	0	-	0
Stage 1	158	-	-	-	-	-
Stage 2	195	-	-	-	-	-
Critical Hdwy	6.42	6.22	4.12	-	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	2.218	-	-	-
Pot Cap-1 Maneuver	645	887	1401	-	-	-
Stage 1	871	-	-	-	-	-
Stage 2	838	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	634	887	1401	-	-	-
Mov Cap-2 Maneuver	634	-	-	-	-	-
Stage 1	856	-	-	-	-	-
Stage 2	838	-	-	-	-	-
Approach	EB	NB		SB		
HCM Control Delay, s	10.4	1		0		
HCM LOS	B					
Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	1401	-	634	887	-	-
HCM Lane V/C Ratio	0.016	-	0.043	0.012	-	-
HCM Control Delay (s)	7.6	0	10.9	9.1	-	-
HCM Lane LOS	A	A	B	A	-	-
HCM 95th %tile Q(veh)	0	-	0.1	0	-	-

***McCORD SQUARE ACCESS DRIVE & JACOBI
LEGACY FARMS ACCESS DRIVE***

CAPACITY ANALYSIS

Intersection												
Int Delay, s/veh	5.7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	14	4	3	29	9	9	8	10	9	4	3	22
Future Vol, veh/h	14	4	3	29	9	9	8	10	9	4	3	22
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	15	4	3	32	10	10	9	11	10	4	3	24
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	67	62	15	61	69	16	27	0	0	21	0	0
Stage 1	23	23	-	34	34	-	-	-	-	-	-	-
Stage 2	44	39	-	27	35	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	926	829	1065	934	822	1063	1587	-	-	1595	-	-
Stage 1	995	876	-	982	867	-	-	-	-	-	-	-
Stage 2	970	862	-	990	866	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	903	822	1065	921	815	1063	1587	-	-	1595	-	-
Mov Cap-2 Maneuver	903	822	-	921	815	-	-	-	-	-	-	-
Stage 1	989	873	-	976	862	-	-	-	-	-	-	-
Stage 2	944	857	-	979	863	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	9.1		9.1			2.2			1			
HCM LOS	A		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1587	-	-	906	922	1595	-	-				
HCM Lane V/C Ratio	0.005	-	-	0.025	0.055	0.003	-	-				
HCM Control Delay (s)	7.3	0	-	9.1	9.1	7.3	0	-				
HCM Lane LOS	A	A	-	A	A	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.1	0.2	0	-	-				

Intersection												
Int Delay, s/veh	4.7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	18	7	6	19	7	6	7	6	33	13	13	19
Future Vol, veh/h	18	7	6	19	7	6	7	6	33	13	13	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	92	92	92	92	92	92	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	20	8	7	21	8	7	8	7	36	14	14	21
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	102	112	25	101	104	25	35	0	0	43	0	0
Stage 1	53	53	-	41	41	-	-	-	-	-	-	-
Stage 2	49	59	-	60	63	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	879	778	1051	880	786	1051	1576	-	-	1566	-	-
Stage 1	960	851	-	974	861	-	-	-	-	-	-	-
Stage 2	964	846	-	951	842	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	858	767	1051	859	775	1051	1576	-	-	1566	-	-
Mov Cap-2 Maneuver	858	767	-	859	775	-	-	-	-	-	-	-
Stage 1	955	843	-	969	857	-	-	-	-	-	-	-
Stage 2	945	842	-	928	834	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	9.3		9.3			1.1			2.1			
HCM LOS	A		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1576	-	-	866	868	1566	-	-				
HCM Lane V/C Ratio	0.005	-	-	0.039	0.04	0.009	-	-				
HCM Control Delay (s)	7.3	0	-	9.3	9.3	7.3	0	-				
HCM Lane LOS	A	A	-	A	A	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.1	0.1	0	-	-				

Intersection				
Intersection Delay, s/veh	3.0			
Intersection LOS	A			
Approach	EB	WB	NB	SB
Entry Lanes	1	1	1	1
Conflicting Circle Lanes	1	1	1	1
Adj Approach Flow, veh/h	22	52	30	31
Demand Flow Rate, veh/h	22	53	30	31
Vehicles Circulating, veh/h	40	35	23	52
Vehicles Exiting, veh/h	43	18	39	36
Ped Vol Crossing Leg, #/h	0	0	0	0
Ped Cap Adj	1.000	1.000	1.000	1.000
Approach Delay, s/veh	2.9	3.1	2.9	2.9
Approach LOS	A	A	A	A
Lane	Left	Left	Left	Left
Designated Moves	LTR	LTR	LTR	LTR
Assumed Moves	LTR	LTR	LTR	LTR
RT Channelized				
Lane Util	1.000	1.000	1.000	1.000
Follow-Up Headway, s	2.609	2.609	2.609	2.609
Critical Headway, s	4.976	4.976	4.976	4.976
Entry Flow, veh/h	22	53	30	31
Cap Entry Lane, veh/h	1325	1331	1348	1309
Entry HV Adj Factor	0.996	0.977	0.993	0.998
Flow Entry, veh/h	22	52	30	31
Cap Entry, veh/h	1320	1301	1338	1306
V/C Ratio	0.017	0.040	0.022	0.024
Control Delay, s/veh	2.9	3.1	2.9	2.9
LOS	A	A	A	A
95th %tile Queue, veh	0	0	0	0

Intersection				
Intersection Delay, s/veh	3.0			
Intersection LOS	A			
Approach	EB	WB	NB	SB
Entry Lanes	1	1	1	1
Conflicting Circle Lanes	1	1	1	1
Adj Approach Flow, veh/h	35	36	51	49
Demand Flow Rate, veh/h	35	36	52	49
Vehicles Circulating, veh/h	49	35	42	37
Vehicles Exiting, veh/h	37	59	42	34
Ped Vol Crossing Leg, #/h	0	0	0	0
Ped Cap Adj	1.000	1.000	1.000	1.000
Approach Delay, s/veh	3.0	2.9	3.1	3.0
Approach LOS	A	A	A	A
Lane	Left	Left	Left	Left
Designated Moves	LTR	LTR	LTR	LTR
Assumed Moves	LTR	LTR	LTR	LTR
RT Channelized				
Lane Util	1.000	1.000	1.000	1.000
Follow-Up Headway, s	2.609	2.609	2.609	2.609
Critical Headway, s	4.976	4.976	4.976	4.976
Entry Flow, veh/h	35	36	52	49
Cap Entry Lane, veh/h	1313	1331	1322	1329
Entry HV Adj Factor	0.996	0.996	0.978	0.994
Flow Entry, veh/h	35	36	51	49
Cap Entry, veh/h	1307	1326	1293	1321
V/C Ratio	0.027	0.027	0.039	0.037
Control Delay, s/veh	3.0	2.9	3.1	3.0
LOS	A	A	A	A
95th %tile Queue, veh	0	0	0	0